


PRODUCT-DETAILS

# OT400E13P

## OT400E13P SWITCH-DISCONNECTOR



### Informations générales

Extension du type de produit	OT400E13P
Code de produit	1SCA106547R1001
EAN	6417019403243
Description courte	OT400E13P SWITCH-DISCONNECTOR
Description longue	4-pole, front operated, base mounted switch-diconnector with black IP65 handle and shaft, terminal bolt kit included

### Valeur Circulaire

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Instructions relatives à la fin de vie	1SCC301118M0201
Informations environnementales	1SCC301266D0201
Environmental Product Declaration - EPD	1SCC301283D0201
REACH Declaration	1SCC011021D0201
Informations RoHS	1SCC011020D0201
Toxic Substances Control	1SCC011025D0201

Act - TSCA

---

## Eco Transparence

---

Environmental Product Declaration - EPD	1SCC301283D0201
---	-----------------

---



---

## Commande

---

Quantité minimum	1 pièce
Code douanier	85365080
Pays d'origine	Finland (FI)

---



---

## Downloads Préférés

---

Fiche produit, informations techniques	1SCC301020C0201
Instructions et manuels	1SCC301035M0019
Mechanical Drawings	1SCC301286F0001 1SCC301285F0001
Environmental Product Declaration - EPD	1SCC301283D0201
Instructions relatives à la fin de vie	1SCC301118M0201

---



---

## Dimensions

---

Produit Largeur Net	240 mm
Produit Hauteur Net	185 mm
Produit Longueur Net	107 mm
Poids net	3.9 kg 8.5 lb

---



---

## Technique

---

Rated Operational Current AC-21A ( $I_g$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A (1000 V) 400 A
Rated Operational Current AC-22A ( $I_g$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A ( $I_g$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Power AC-23A ( $P_g$ )	(220 ... 240 V) 132 kW (400 ... 415 V) 230 kW (500 V) 280 kW (690 V) 400 kW
Courant thermique conventionnel à l'air libre ( $I_{th}$ )	$\Theta = 40\text{ °C}$ 400 A

---

Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 400 A
Tension assignée de tenue aux chocs ( $U_{imp}$ )	12 kV
Tension assignée d'isolement ( $U_i$ )	acc. to IEC/EN 60664-1 1000 V
Tension Rated Short-Circuit Making Capacity ( $I_{cm}$ )	Circuit principal 1000 V (690 V) 65 kA
Courant assigné de courte durée admissible ( $I_{cw}$ )	for 1 s 15 kA
Power Loss	at Rated Operating Conditions per Pole 10 W
Degré de pollution	3
Handle Color	Black
Handle Type	Handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism Between the Poles 13 (Between the Poles)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Mode de fonctionnement	Front operated
Normes et standards	IEC 60947-3
Fonctions spéciales	No
Type de montage	Base mounting
Nombre de pôles	4
Indice de protection	Front IP00
Type de borne	Lug terminals
Couple de serrage	acc. IEC 60947-1 30 ... 44 N·m
Durabilité mécanique	16000
Lock Type	Yes

## Technique UL/CSA

Couple de serrage	acc. IEC 60947-1 30 ... 44 N·m
-------------------	--------------------------------

## Environnement

Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations environnementales	1SCC301266D0201
Toxic Substances Control Act - TSCA	1SCC011025D0201

## Certificats et Déclarations (Numéro de document)

Déclaration de Conformité	1SCC301135D2704
---------------------------	-----------------

- CE

DNV GL Certificate

1SCC301174D0204

REACH Declaration

1SCC011021D0201

## Emballage

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	220 mm 8.7 in
Emballage Niveau 1 Longueur	260 mm 10.2 in
Emballage Niveau 1 Hauteur	155 mm 6.1 in
Emballage Niveau 1 Poids	4.2 kg 9.3 lb
Emballage Niveau 1 EAN	6417019403243

## Classifications

Code de classification d'objet	Q
ETIM 7	EC000216 - Switch disconnector
ETIM 8	EC000216 - Switch disconnector
ETIM 9	EC000216 - Switch disconnector (low voltage)
eClass	V11.1 : 27371403
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)

## Catégories

Produits basse tension → Interrupteurs → Interrupteurs-sectionneurs

