

PRODUCT-DETAILS

# B24 352-100

## B24 352-100, Energy meter'Silver', Modbus RS485, Three-phase, 1 A



### Informations générales

Extension du type de produit	B24 352-100
Code de produit	2CMA100183R1000
ABB désignation de type	B24 352-100
EAN	7392696001830
Description courte	B24 352-100, Energy meter'Silver', Modbus RS485, Three-phase, 1 A

Description longue	<p>Advanced compact DIN-rail meter with an easy to read back lighted display. The meter is intended for use in the commercial or residential buildings etc. The meter can be used in 3 or 4 wire systems. The meter has several instrumentation values, 25 possible alarms and event logs. Three phase transformer connected for active and reactive energy. Import and export of energy in different registers and one total. Resettable register for intermediate values. Up to four tariffs. Two outputs and inputs for pulses or alarm etc. RS-485 communication over Modbus RTU or EQ Bus. Accuracy class 0,5 (or C for MID meters). The meters is IEC approved + MID approved and verified.</p>
--------------------	---

### Eco Transparence

Environmental Product Declaration - EPD	9AKK108467A4138
---	-----------------

### Technique

Normes et standards	EN 50470-1
Fonction	Electricity meter
Sub-Function	Silver
Tension nominale (U <sub>n</sub> )	3x220-240 V
Voltage Range	3x176...276 V
Courant nominal (I <sub>n</sub> )	1 A Maximum 6 A
Intensité de courant	1 A
Fréquence assignée (f)	50 / 60 Hz
	0.721 W
Interface de communication	Modbus RS485
Précision	Active Energy Class C MID (±0.5%)
Measuring Instrument Conformity	Measurement Instrument Directive (MID)
Meter Tariff Control	External
Meter Tariff Rating	Multi-Tariff
Pulse Output Rate	1-999999
Nombre de pôles	4
Nombre de phases	Three-phase
Number of Counter Positions	7
Nombre d'entrées/sorties numériques	2 DI 2 DO
Meter Type	Transformer connected
Type de montage	DIN-Rail
Pulse Output Type	Electrical
Type d'affichage	Digital
Matériau du boîtier	Polycarbonate in transparent front glass. Glass reinforced polycarbonate in bottom case and upper case. Polycarbonate in terminal cover.
Option E/S	2 digital output, 2 digital input
Additional Information	CT (1A, 5A)
Communication	Modbus RTU
Connecting Capacity Main Circuit	0.5 ... 10 mm <sup>2</sup>

## Environnement

Température de l'air ambiant	Operation -40 ... 70 °C
Indice de protection	IP20
Statut RoHS	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Informations RoHS	2CMC485007
Informations environnementales	2CMC485003D0001
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Dimensions

Width in Number of Modular Spacings	4
Produit Largeur Net	70 mm
Produit Hauteur Net	26.5 mm
Produit Longueur Net	65 mm
Poids net	0.27 kg
Taille	96X70X65

## Commande

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Poids	0.35 kg
E-Number (Finland)	6625045
E-Number (Sweden)	0900049

## Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CMC485002D0001
--------------------------------	-----------------

## Installation

Instructions et manuels	2CMC485019M0201
-------------------------	-----------------

## Downloads Préférés

Fiche produit, informations techniques	2CMC485003M0201
--	-----------------

## Classifications

ETIM 8	EC001506 - Kilowatt-hour meter
ETIM 9	EC001506 - Kilowatt-hour meter
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	90283019
eClass	V11.0 : 27142316
Code de classification d'objet	P

## Accessories

Identifiant	Description	Type	Quantity	Unit Of Measure
2CSG225995R1101	CT MAX 1000 Current transformer	CT MAX 1000	1	piece

2CSG226055R1101	CT MAX 1000 SELV Current transformer	CT MAX 1000 SELV	1	piece
2CSG225945R1101	CT MAX 300 Current transformer	CT MAX 300	1	piece
2CSG226005R1101	CT MAX 300 SELV Current transformer	CT MAX 300 SELV	1	piece
2CSG225955R1101	CT MAX 400 Current transformer	CT MAX 400	1	piece
2CSG226015R1101	CT MAX 400 SELV Current transformer	CT MAX 400 SELV	1	piece
2CSG225965R1101	CT MAX 500 Current transformer	CT MAX 500	1	piece
2CSG226025R1101	CT MAX 500 SELV Current transformer	CT MAX 500 SELV	1	piece
2CSG225975R1101	CT MAX 600 Current transformer	CT MAX 600	1	piece
2CSG226035R1101	CT MAX 600 SELV Current transformer	CT MAX 600 SELV	1	piece
2CSG225985R1101	CT MAX 800 Current transformer	CT MAX 800	1	piece
2CSG226045R1101	CT MAX 800 SELV Current transformer	CT MAX 800 SELV	1	piece
2CSG225785R1101	CT PRO XT 100 Current transformer	CT PRO XT 100	1	piece
2CSG225885R1101	CT PRO XT 100 SELV Current transformer	CT PRO XT 100 SELV	1	piece
2CSG225795R1101	CT PRO XT 150 Current transformer	CT PRO XT 150	1	piece
2CSG225895R1101	CT PRO XT 150 SELV Current transformer	CT PRO XT 150 SELV	1	piece
2CSG225805R1101	CT PRO XT 200 Current transformer	CT PRO XT 200	1	piece
2CSG225905R1101	CT PRO XT 200 SELV Current transformer	CT PRO XT 200 SELV	1	piece
2CSG225815R1101	CT PRO XT 250 Current transformer	CT PRO XT 250	1	piece
2CSG225915R1101	CT PRO XT 250 SELV Current transformer	CT PRO XT 250 SELV	1	piece
2CSG225825R1101	CT PRO XT 300 Current transformer	CT PRO XT 300	1	piece
2CSG225925R1101	CT PRO XT 300 SELV Current transformer	CT PRO XT 300 SELV	1	piece
2CSG225745R1101	CT PRO XT 40 Current transformer	CT PRO XT 40	1	piece
2CSG225845R1101	CT PRO XT 40 SELV Current transformer	CT PRO XT 40 SELV	1	piece
2CSG225835R1101	CT PRO XT 400 Current transformer	CT PRO XT 400	1	piece
2CSG225935R1101	CT PRO XT 400 SELV Current transformer	CT PRO XT 400 SELV	1	piece
2CSG225755R1101	CT PRO XT 50 Current transformer	CT PRO XT 50	1	piece
2CSG225855R1101	CT PRO XT 50 SELV Current transformer	CT PRO XT 50 SELV	1	piece
2CSG225765R1101	CT PRO XT 60 Current transformer	CT PRO XT 60	1	piece
2CSG225865R1101	CT PRO XT 60 SELV Current transformer	CT PRO XT 60 SELV	1	piece
2CSG225775R1101	CT PRO XT 80 Current transformer	CT PRO XT 80	1	piece
2CSG225875R1101	CT PRO XT 80 SELV Current transformer	CT PRO XT 80 SELV	1	piece

2CCG000242R0001	SCU100 Control unit	SCU100	1	piece
2CDG110226R0011	QA/S3.16.1 Energy Analyzer, M-Bus, 16 Devices, MDRC	QA/S3.16.1	1	piece
2CDG110227R0011	QA/S3.64.1 Energy Analyzer, M-Bus, 64 Devices, MDRC	QA/S3.64.1	1	piece
2CDG110228R0011	QA/S4.16.1 Energy Analyzer, Modbus RTU, 16 Devices, MDRC	QA/S4.16.1	1	piece
2CDG110229R0011	QA/S4.64.1 Energy Analyzer, Modbus RTU, 64 Devices, MDRC	QA/S4.64.1	1	piece
2CDG110224R0011	QA/S1.16.1 Energy Analyzer, KNX, 16 Devices, MDRC	QA/S1.16.1	1	piece

---

## Catégories

---

Produits basse tension → Appareillage modulaire et parafoudres → Compteurs d'énergie → Compteurs d'énergie

