

## Features

Use: Indoor  
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK  
Emission: DIRECT  
Optics: OPAL  
Colour: CAFFE  
Dimming: PUSH, DALI  
Emergency: NO  
L: 1960mm  
A: 53mm  
H: 69mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 5kg

## Tech data

Luminaire input power: 48.3W  
Luminaire luminous flux: 3757lm  
IP: 40  
Insulation class: I  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 42W  
Colour temperature: 4000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

## Standards


Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



## COMPLETION ACCESSORIES


---



HERO: MOD.CIECO 250 CAF

**108676.20**


---



HERO: MOD.CIECO ANG.SX 150 CAF

**108677.20**


---



HERO: MOD.CIECO ANG.DX 150 CAF

**108678.20**


---



HERO: MOD.CIECO 1120 CAF

**108679.20**


---



HERO: MOD.CIECO 1400 CAF

**108680.20**


---



HERO: MOD.CIECO 1680 CAF

**108681.20**

---



HERO: COPPIA TESTATE CAF

**108684.20**

## MOUNTING ACCESSORIES



HERO: SOSPL3000 1PZ. TESTA/CODA

**108685.99**



HERO: SOSPL3000 1PZ. UNIONE

**108686.99**



HERO: STAFFA PARETE "L" CAF

**108687.20**




HERO: KIT INCASSO LED (1X)

**108688.99**



HERO: SPESS. CARTONG. 10MM 2PZ.

**108689.99**




KIT ALIMENTAZIONE L1200 5P BIA

**108921.01**




KIT ALIMENTAZIONE L1200 5P CAF

**108921.20**



KIT ALIMENTAZIONE L3000 5P BIA

**108922.01**



KIT ALIMENTAZIONE L3000 5P CAF

**108922.20**