

PRODUCT-DETAILS

JSHD4-1

JSHD4-1 Three-position handheld device - Top part



Informations générales

Extension du type de produit	JSHD4-1
Code de produit	2TLA020006R2100
EAN	7350024459722
Description courte	JSHD4-1 Three-position handheld device - Top part
Description longue	<p>The JSHD4-3 is a top part of a three-position device JSHD4. It has no LEDs and no extra buttons. It must be used with one of the following bottom parts: AB, AD, AH, AJ, AK, AL.</p> <p>Anti-tamper can be chosen as option with all except bottom part AK.</p> <p>Three-position devices are used to allow a limited movement of the machine when the operator is in the dangerous area, for example during troubleshooting, test running and programming.</p>

Commande

Quantité minimum	1 pièce
Code douanier	85369095
Groupe de produit	JSHD4
Type de produit	Three-position handheld device - Top part
Sub-Function	No auxiliary button
Sub-Function 2	Holder for Eva (home position) with bottom part AL
Status Indicator	Non

Downloads Préférés

Fiche produit, informations techniques	2TLC010001C0202
Instructions et manuels	2TLC172072M0201
Wiring Diagram	2TLC010143D0201
CAD Dimensional Drawing	2CDC001079B0201
Marketing Video	2TLC010018N0201

Dimensions

Produit Longueur Net	340 mm
Produit Hauteur Net	157 mm
Produit Largeur Net	56 mm
Poids net	0.139 kg

Safety Information

Performance Level (PL)	Up to e
B10d Value	Operations to Bottom Position 968 000 Operations to Middle Position 2 million

Technique

Interface de communication	Contacts
Configuration Connexion	Depends on bottom part
Maximum Switching Current	Circuit principal 0.02 mA
Maximum Switching Voltage	Circuit principal 30 V
Minimum Switching Capacity	Main Circuit 8 mA, 10 VDC
Number of Contacts CO	1
Number of Contacts NC	0
Number of Contacts NO	1
Rated Operational Current DC-12 (I_{θ})	(24 V) 0.02 A
Tension	24 V DC
Informations techniques	Operating force: Approx. 15 N for three-position button (ON), Approx. 45 N for three-position button (OFF), Approx. 2.5 N for top/front pushbutton; Mechanical service life: 1 million cycles, top to middle position, 100 000 cycles, middle to bottom position, and top/front push button

Technique UL/CSA

Enclosure Type UL/CSA	1
-----------------------	---

Environnement

Température de l'air ambiant	Operation -10 ... +70 °C
Indice de protection	IP65
Matériau	Handle: Polyamide and Noryl Rubber: Neoprene
REACH Declaration	2CMT2022-006480
Informations RoHS	2CMT2022-006499
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificats et Déclarations (Numéro de document)

CQC Certificate	No certification needed
Certificat ecULus	2TLC010062D0201
Declaration of Conformity - CCC	No declaration needed
Déclaration de Conformité - CE	2TLC172022D0201
Declaration of Conformity - UKCA	2TLC010152D0201

Emballage

Emballage Niveau 1 Unités	1 pièce
Emballage Niveau 1 Largeur	0.286 m
Emballage Niveau 1 Longueur	0.126 m
Emballage Niveau 1 Hauteur	0.103 m
Emballage Niveau 1 Poids	0.283 kg
Emballage Niveau 1 EAN	7350024459722

Classifications

eClass	V11.0 : 27371238
ETIM 7	EC002571 - Agreement switch
ETIM 8	EC002571 - Agreement switch
ETIM 9	EC002571 - Agreement switch
Code de catégorie granulaire IDEA (IGCC)	5219 >> Switch part or accessory
UNSPSC	39122221
Code de classification d'objet	B

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Produits pour la sécurité → Commandes → Poignée à trois positions JSHD4

