

IONA CAMPER VAN TERMINAL DISTRIBUTION WATER+ELECTRICITY FOR 1 VEHICLE WITH MARKER LIGHTING

Article code 58051B



Function:

- **Energy distribution:** water + electricity

Technical description:

Description of the IONA Camper Van terminal and its toilet water collector:

- Aluminium 20/10th terminal
- **Exterior dimensions:** H1000 x W430 x D285 mm
- 1 compartment, 1 door in rear position
- Closure by retractable rotating handle with 1/2 key cylinder 455/455E + 3-pt casement bolt
- Fixing to base in concrete previously poured on site
- **Protection indices:** IP44- IK10
- Colour: grey (RAL9007) epoxy paint

Water equipment:

- Free access to water
- 1 x 20/27 male connection for supply
- 1 shut-off valve with bleeder valve
- 1 manual 1/4 turn draw-off tap on the left side of the terminal
- 1 Presto tap for rinsing the toilet water tank on the façade of the terminal
- 1 timed push-button tap for rinsing the toilet water collector on the façade of the terminal
- 316 litre passivated stainless steel toilet water collector with flushing and closing hatch
- **Overall collector dimensions:** H67 x W450 x D274 mm
- Fixing in front and against the terminal on the concrete base

IONA CAMPER VAN TERMINAL DISTRIBUTION WATER+ELECTRICITY FOR 1 VEHICLE WITH MARKER LIGHTING

Article code 58051B

Water/electricity separation partition

Electrical equipment:

- 1 tetrapolar distribution terminal block 25 mm² (max. 50 mm² rigid)
- 1 earthing terminal
- 1 lockable 63A switch
- 1 differential circuit breaker Uni+Neutral 16A-30 mA Curve C
- 1 socket IP44 2P+T 16A, type CEE17 on the left side of the terminal
- 1 LED marker light
- 1 circuit breaker protection for marker lighting

Area(s) of use:

- Mobile home and chalet pitches
- Use and distribution of the low voltage electric network up to 440 V
- Emergent products from underground networks installed outside the private estate at the limit of the plot

Technical data:

Description	Value	Standards
Operating T	-25°C to + 40°C	
Material	Aluminium	
Installation method	installation on the ground	
With reset hatch	No	
Marker lighting	Yes	
No. of sockets CEE 16A/230V 2P+T	1	
Circuit breaker outlets calibre (A)	16	
Connection capacity	Electricity Copper cable up to 25mm ² Aluminium cable up to 25mm ² Water 20/27 mm male connector	
Number of taps	1	
With change machine	No	