
# 1SNK922302R0000 ACTIVE



### ENTRELEC | ENTRELEC SNK

TE Internal #: 1SNK922302R0000

Terminal Block & Strip Conducting Accessories, Jumper Bar, 2 Pole, Product Spacing .866 in [22 mm], -67 – 230 °F [-55 – 110 °C],

ENTRELEC SNK

View on TE.com >



Connectors > Terminal Blocks & Strips > Terminal Block & Strip Accessories > Terminal Block & Strip Conducting Accessories



Conducting Accessory Type: Jumper Bar

Number of Poles: 2

PCB Mount Retention Type: Screw Product Spacing: 22 mm [.866 in] Contact Current Rating (Max): 192 A

#### **Features**

### **Product Type Features**

Conducting Accessory Type	Jumper Bar
Configuration Features	
Number of Poles	2
Electrical Characteristics	
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	600 V
Impulse Withstanding Voltage Rating (IEC)	8000 V
Voltage Rating (CSA)	600 V
Current Rating (CSA)	175 A
Power Loss	6.1 W
Dielectric Test Voltage	2200 V
Short-Time Withstanding Current Rating @ 1s	8400 A
Voltage Rating (IEC)	1000 V
Current Rating (UL)	175 A
Current Rating (IEC)	192 A
Body Features	
Product Weight	27 g[.952 oz]

Polyamide

Plastic & Resin Material Type



#### **Contact Features**

Contact Current Rating (Max)	192 A
Mechanical Attachment	
Tightening Torque	17.7 in-lbs
PCB Mount Retention Type	Screw
Dimensions	
Tool Size	4 mm[.157 in]
Product Depth	20.7 mm[.815 in]
Product Width	22 mm[.866 in]
Product Height	35 mm[1.378 in]
Product Spacing	22 mm[.866 in]
Usage Conditions	
Storage Temperature Range	-55 – 110 °C[-67 – 230 °F]
Installation Temperature Range	-5 - 40 °C[23 - 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]
Industry Standards	
IP Rating	IP20

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as



EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

### **Compatible Parts**













## Also in the Series | ENTRELEC SNK







Terminal Block & Strip Conducting Accessories(67)



Terminal Block & Strip Insulating Accessories(30)

# Customers Also Bought

Terminal Block & Strip Conducting Accessories, Jumper Bar, 2 Pole, Product Spacing . 866 in [22 mm], -67 – 230 °F [-55 – 110 °C], ENTRELEC SNK





TE Part #1SNA400305R1000 D70/22



TE Part #1SNK506020R0000 ZS6-BL



TE Part #1SNK516020R0000 ZS35-BL





TE Part #1SNK522150R0000 ZS70-PE



TE Part #1SNA110440R0700

D4/6.NLP

TE Part #1SNA115149R2000 M300/42.FF



#### **Documents**

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1SNK922302R0000\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1SNK922302R0000\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1SNK922302R0000\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

### Datasheets & Catalog Pages

Catalogue - ENTRELEC terminal-blocks-sna-series

English

**ENTRELEC Terminal Block - Master Catalog** 

English

Terminal Block & Strip Conducting Accessories, Jumper Bar, 2 Pole, Product Spacing . 866 in [22 mm], -67 – 230 °F [-55 – 110 °C], ENTRELEC SNK



JB22-2

English

**SNK SERIES TERMINAL BLOCKS** 

English

**ENTRELEC Terminal Blocks Catalogue (RUS)** 

**Essential Entrelec Terminal Blocks** 

French

**Essential Entrelec Terminal Blocks** 

English

Product Environmental Compliance

**Product Compliance** 

English

**Product Compliance** 

English