

61723360	DATA SHEET
Valid from: 13.08.2021	Detectable Cable ties with steel nose (TY-RAP®)


The detectable cable ties are made of polyamide and can be used in many different applications, due to his features. Due to his material features, the cable tie can be detected by different systems.



Material: Polyamide 6.6 with steel nose
Polypropylene with steel nose

Technical Features:

Bundle diameter 1 up to 102mm
 Bandwidth 2,3 up to 7,0 mm
 Tensile strength 50 up to 540N
 Temperature range -60°C up to +85°C
 Installations temperature -20°C up to +65°C



Additional features:

Fire Classification HB acc. to UL 94
 Resistant to Solvents, oils and greases
 Detected by X-Ray inspection equipment, metal detector and optical identification systems
 UV-Resistant
 Floatable only Polyproylen

Color: Blue

Norm Reference:



HACCP nach EU-Verordnung Nr. 852/2004

Dimensions:

Part No.	Bundle diameter mm		Size mm		Tensile strength N
	min.	max.	Length	Wide	
Trade TY-RAP® PA6.6					
6172 3351	1,5	16,0	92	2,3	80
6172 3359	2,0	29,0	140	3,6	160
6172 3352	3,0	45,0	186	4,6	200
6172 3353	4,8	102,0	345	4,8	220
6172 3354	4,8	102,0	361	6,9	540
Trade TY-RAP® Polypropylene					
6172 3355	2,0	16,0	92	2,4	50
6172 3356	3,5	45,0	186	4,8	130
6172 3357	3,5	102,0	360	4,8	130
6172 3358	6,0	90,0	340	7,0	270

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.