

Part number

MFVN 06 LG25



Hood, LS-TYPE series, with 1 lever, M25 top cable entry without adapter, size "44.27", high construction

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 1 lever
Size	Size 44.27
Cable entry	Top cable entry M25
Specification	High construction

Technical data

IP degree of protection	IP65
Further technical details	
Weight	170,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Other materials	Lever: Polyamide (PA) Gasket: NBR
Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747187398
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information


Sub-packaging weight	0,85 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747188180

Part number

MFVN 06 LG25



Catalogue drawings



Catalogue drawings

CH..N - MF..N enclosures		size "44.27"	LS-TYPE version																					
<p>inserts:</p> <table border="1"> <tr><td>CDD</td><td>24 poles + Ⓞ</td><td>59 *</td></tr> <tr><td>CQE</td><td>10 poles + Ⓞ</td><td>80 *</td></tr> <tr><td>CSH</td><td>6 poles + Ⓞ</td><td>88 *</td></tr> <tr><td>CCE</td><td>6 poles + Ⓞ</td><td>94 *</td></tr> <tr><td>CNE, CSE, JONE, JCSE</td><td>6 poles + Ⓞ 95 and 103</td><td>118 *</td></tr> <tr><td>CSS</td><td>6 poles + Ⓞ</td><td>118 *</td></tr> <tr><td>MIXO</td><td>2 modules</td><td>160+195 *</td></tr> </table> <p>insert centre distance: 44 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	CDD	24 poles + Ⓞ	59 *	CQE	10 poles + Ⓞ	80 *	CSH	6 poles + Ⓞ	88 *	CCE	6 poles + Ⓞ	94 *	CNE, CSE, JONE, JCSE	6 poles + Ⓞ 95 and 103	118 *	CSS	6 poles + Ⓞ	118 *	MIXO	2 modules	160+195 *	<p>hoods with 2 pegs</p>	<p>covers</p>	
CDD	24 poles + Ⓞ	59 *																						
CQE	10 poles + Ⓞ	80 *																						
CSH	6 poles + Ⓞ	88 *																						
CCE	6 poles + Ⓞ	94 *																						
CNE, CSE, JONE, JCSE	6 poles + Ⓞ 95 and 103	118 *																						
CSS	6 poles + Ⓞ	118 *																						
MIXO	2 modules	160+195 *																						
<p>description</p> <p>with lever and gasket, top entry with lever and gasket, top entry, high construction</p>	<p>part no.</p> <p>entry</p> <p>M</p>	<p>part no.</p>																						
<p>covers with pegs covers with lever</p>	<p>dimensions in mm</p> <p>MHVN 06 LG25</p> <p>MFVN 06 LG25</p>	<p>dimensions in mm</p> <p>CHCN 06 L</p> <p>CHCN 06 LG</p>																						
<p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>																								
<p>dimensions shown are not binding and may be changed without notice</p>																								

Notes

Dimensions shown in mm are not binding and may be changed without notice.