

## Features

Use: Indoor  
 Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK  
 Emission: DIRECT  
 Optics: MICRO OPTICS  
 Colour: CAPPUCCINO  
 Dimming: PUSH, DALI  
 Emergency: NO  
 L: 868mm  
 A: 53mm  
 H: 69mm  
 Made in: ITALY  
 Warranty: 5 years

## Tech data

Luminaire input power: 26.5W  
 Luminaire luminous flux: 2183lm  
 IP: 40  
 Insulation class: I  
 Supply voltage: 220-240V 50/60Hz  
 UGR: <19  
 SELV: Si

## Source

Light source: LED  
 Source power: 22W  
 Colour temperature: 3000K  
 CRI: >90  
 Colour tolerance: 3 Step MacAdam  
 LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

## Standards


Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
 CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



## COMPLETION ACCESSORIES


---



HERO: MOD.CIECO ANG.SX 150 CAP

108677.21


---



HERO: MOD.CIECO 1120 CAP

108679.21


---



HERO: MOD.CIECO 1680 CAP

108681.21


---



HERO: COPPIA TESTATE CAP

108684.21


---



HERO: MOD.CIECO 1400 CAP

108680.21


---



HERO: MOD.CIECO 250 CAP

108676.21

---



HERO: MOD.CIECO ANG.DX 150 CAP

108678.21

## MOUNTING ACCESSORIES




KIT ALIMENTAZIONE L1200 5P BIA

108921.01



HERO: SOSPL3000 1PZ. TESTA/CODA

108685.99



KIT ALIMENTAZIONE L3000 5P BIA

108922.01




HERO: SPESS. CARTONG. 10MM 2PZ.

108689.99



HERO: SOSPL3000 1PZ. UNIONE

108686.99




ALL-TRACK: COPPIA ADATT. 3P+DALI NER

106723.02



KIT ALIMENTAZIONE L1200 5P CAP

**108921.21**



ALL-TRACK: COPPIA ADATT. 3P+DALI BIA

**106723.01**



HERO: KIT INCASSO LED (1X)

**108688.99**



KIT ALIMENTAZIONE L3000 5P CAP

**108922.21**



HERO: STAFFA PARETE "L" CAP

**108687.21**