




- 1. MATERIAL: BODY - COPPER SCREW - STEEL, ZINC PLATED
- 2. TWO PIECE FLOATING TONGUE ASSEMBLY.
- 3. CULUS LISTED FOR USE UP TO 600V AND TEMPERATURE RATED 90°C
- 4. RATED FOR USE WITH COPPER STRANDED CODE CONDUCTOR ONLY
- 5. THESE PARTS ARE ROHS COMPLIANT
- 6. PKG. QTY.: L = 50 C = 100





PANDUIT PART NUMBER	STRANDED	SCREW TORQUE IN-LB [N.m]	STUD SIZE (IN)	DIMENSIONS - IN [mm] ± .03 [0.8]									SCREW		
	COPPER WIRE RANGE			D DIA	G	F±.05[1.3]	W	A±.05 [1.3]	М	T	Н	L	C (REF)	X±5° (REF)	STYLE
CB\$35-36-C	14 AWG - 6 AWG	13 IN-LB [1.5 N.m]	3/16"	0.20 [5.0]	0.22 [5.6]	0.43 [10.9]	0.39 [9.9]	1.29 [32.8]	0.47 [11.9]	0.06 [1.5]	0.55 [14.0]	0.36 [9.1]	0.30 [7.6]	90	5/64" HEX SOCKET
CB\$35-14-C	14 AWG - 6 AWG	13 IN-LB [1.5 N.m]	1/4"	0.26 [6.6]	0.26 [6.6]	0.43 [10.9]	0.50 [12.7]	1.43 [36.3]	0.47 [11.9]	0.06 [1.5]	0.55 [14.0]	0.36 [9.1]	0.41 [10.4]	90	5/64" HEX SOCKET
CBS70-14-L	8 AWG - 2 AWG	8 AWG = 20 IN-LB [2.3 N.m] 6 AWG = 23 IN-LB [2.6 N.m] 4-2 AWG = 35 IN-LB [4.0 N.m]	1/4"	0.26 [6.6]	0.25 [6.4]	0.55 [14.1]	0.50 [12.7]	1.55 [39.4]	0.53 [13.5]	0.08 [2.1]	0.65 [16.6]	0.46 [11.6]	0.44 [11.1]	87	1/8" HEX SOCKET

							CBS SERIES COPPER MECHANICAL LUGS
							CUSTOMER DRAWING
		<u> </u>					ITEM REVISION NAME 14J226CO/03
					ADDED REFERENCE ANGLE DIMENSION X		DATASET FILE NAME 14J226CO-DC/03.SLDDRW
03	9/21	JHNU	TMR	JADE	DIMENSION F: .55 +/05 WAS .55 +/03	106551	UNLESS OTHERWISE SPECIFIED, MATERIAL
02	3/21	JHNU	TMR	JADE	REVISED PACKAGING CODE: CBS70-14-L WAS CBS70-14-C	098745	DIMENSIONAL TOLERANCES ARE: IN [mm]
01	3/21	JHNU	TMR	JADE	CBS70-14-C RELEASED, CBS125-14-Q REMOVED	098721	.X ± .XXX ± SEE NOTES .XX ± ANGLES ±
00	10/20	JHNU	TMR	ALP	DRAWING RELEASED	089914	THIRD ANGLE PROJECTION DRAWING NUMBER 14J226CO-DC
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	DRAWN BY DATE CHK SCALE JHNU 10/20 TMR N/A SHEET 1 OF 1 B