1SET314060R0000 - ACTIVE

ENTRELEC | M12 Connector

TE Internal #: 1SET314060R0000


M12 Pigtail Cable Assembly, 5 Position, 3 m, Sensor/Actuator,

Code A, M12 Plug, Shielded, Single Ended, GF Nylon

View on TE.com >



Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies



M8/M12 Application Type: Sensor/Actuator

Number of Positions: 5

Keying Code: A

Connector Type (End A): M12 Plug
Cable Assembly Type: M12 Pigtail

Features

Product Type Features

LED	Without
Product Type	Cable Assembly
Cable Type	PUR
Assembly Type	Pigtail
Connector Type (End A)	M12 Plug
Cable Assembly Type	M12 Pigtail
Configuration Features	
Number of Positions	5
Keying Code	A
Electrical Characteristics	
Operating Voltage	60 VDC
Body Features	
Cable Exit Angle	Straight
Environmental Protection	With



Conductor Material	Copper Alloy
Connector Color	Blue
Cable Jacket Color	Gray
Insulation Material	PVC
Contact Features	
Contact Current Rating	4 A
Mechanical Attachment	
Screw & Hole Thread Size	M12
Connector Orientation (End A)	Straight
Housing Features	
Housing Material	GF Nylon
Dimensions	
Dimensions Wire Size	22 AWG
	22 AWG
Wire Size	22 AWG Sensor/Actuator
Wire Size Operation/Application	
Wire Size Operation/Application M8/M12 Application Type	Sensor/Actuator
Wire Size Operation/Application M8/M12 Application Type Shielded	Sensor/Actuator
Wire Size Operation/Application M8/M12 Application Type Shielded Packaging Features	Sensor/Actuator Yes
Wire Size Operation/Application M8/M12 Application Type Shielded Packaging Features Packaging Method	Sensor/Actuator Yes
Wire Size Operation/Application M8/M12 Application Type Shielded Packaging Features Packaging Method Other	Sensor/Actuator Yes Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) SVHC > Threshold: Pb (1.9% in Component Part)



Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content	Not Low Halogen - contains Br or Cl > 900
	ppm.

Solder Process Capability

Not reviewed for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



Also in the Series M12 Connector



Documents

Product Drawings M12-MS-5P-PUR-3.0-SH

English

CAD Files

M12 Pigtail Cable Assembly, 5 Position, 3 m, Sensor/Actuator, Code A, M12 Plug, Shielded, Single Ended, GF Nylon



3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SET314060R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SET314060R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SET314060R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Infographic - entrelec ews-linecard

English

Catalog - ENTRELEC-M8-M12-RJ45

English

Product Specifications

Application Specification

English