
ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 > 0 - 2. WITHDRAL AT 2



Product type designation General characteristics Colour Type of positions Material EC degree of protection Mechanical features Mechanical life Cycles Mounting adapter Mounting adapter UL degree of protection LPFS38 Black Aluminium and zinc alloy IP66, IP67 and IP69K Without mounting adapter LPXAU120M UL technical data UL degree of protection Type1, 2, 3R, 4, 4X, 12, 12K Ambient conditions
ColourBlackType of positionsSelector switchMaterialAluminium and zinc alloyIEC degree of protectionIP66, IP67 and IP69KMechanical featuresWithout mounting adapterFixingWithout mounting adapterMounting adapterLPXAU120MUL degree of protectionType1, 2, 3R, 4, 4X, 12, 12K
Type of positions Material EC degree of protection IEC degree of protection Mechanical features Mechanical life Cycles Without mounting adapter Mounting adapter UL degree of protection Selector switch Aluminium and zinc alloy IP66, IP67 and IP69K Wechanical life Cycles 1000000 Without mounting adapter LPXAU120M UL technical data UL degree of protection Type1, 2, 3R, 4, 4X, 12, 12K
Material Aluminium and zinc alloy IEC degree of protection Mechanical features Mechanical life Cycles 1000000 Fixing Without mounting adapter Mounting adapter Mounting adapter UL technical data UL degree of protection Aluminium and zinc alloy IP66, IP67 and IP69K Without mounting adapter LPXAU120M Type1, 2, 3R, 4, 4X, 12, 12K
Material zinc alloy IEC degree of protection IP66, IP67 and IP69K Mechanical features Mechanical life cycles 1000000 Fixing Without mounting adapter Mounting adapter Mounting adapter UL technical data UL degree of protection Type1, 2, 3R, 4, 4X, 12, 12K
Mechanical features Mechanical life cycles 1000000 Fixing Without mounting adapter Mounting adapter UL technical data UL degree of protection IP69K Without mounting adapter LPXAU120M Type1, 2, 3R, 4, 4X, 12, 12K
Mechanical lifecycles1000000FixingWithout mounting adapterMounting adapterLPXAU120MUL technical dataType1, 2, 3R, 4, 4X, 12, 12K
Fixing Without mounting adapter Mounting adapter LPXAU120M UL technical data UL degree of protection Type1, 2, 3R, 4, 4X, 12, 12K
Mounting adapter LPXAU120M UL technical data UL degree of protection Type1, 2, 3R, 4, 4X, 12, 12K
UL technical data UL degree of protection Type1, 2, 3R, 4, 4X, 12, 12K
UL degree of protection Type1, 2, 3R, 4, 4X, 12, 12K
4X, 12, 12K
Ambient conditions
Temperature
Operating temperature
min °C -25
max °C +70
Storage temperature
min °C -40
max °C +85

Dimensions



Certifications and compliance

Compliance

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1 UL508

Certificates

cULus

ETIM classification





ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 > 0 - 2. WITHDRAL AT 2

ETIM 8.0

EC002611 -Control switch