



Features

Use: Indoor
Type of installation: TRACK
Emission: ADJUSTABLE
Optics: SPOT
Beam: 15 - 38°
Colour: WHITE
Dimming: DALI
Emergency: NO
L: 275mm
A: Ø65mm
H: 155mm
Warranty: 5 years

Tech data

Luminaire input power: 30W
IP: 20
Insulation class: II
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 30W
Source luminous flux: 2770lm
Colour temperature: 4000K
CRI: >90
LED lifespan: 30000h L70 B20

Compliance



CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



SCREENS



DALÌ : LENTE 55° PER 30W


106114.00

COMPLETION ACCESSORIES



DALÌ : INSERTO ORO OPACO PER 30W

106110.15



DALÌ : HONEYCOMB PER 30W

106112.02