

# TUBE FLUORESCENT



## TUBE MINIATURE T4 ET T5

T12 (FD). Tubes miniatures.

T4		G5 Ø12 230V 6 000 h		
P (w)	L (mm)	Lumens	Teinte	Code
6	205	265	○4000 K	<b>2570</b>
6	205	258	○6400 K	<b>2655</b>
8	327	380	○4000 K	<b>2571</b>
8	327	370	○6400 K	<b>2656</b>
12	355	570	○4000 K	<b>2572</b>
12	355	550	○6400 K	<b>2657</b>
16	454	1000	○4000 K	<b>2573</b>
16	454	960	○6400 K	<b>2658</b>
20	550	1450	○4000 K	<b>2574</b>
20	550	1400	○6400 K	<b>2659</b>
24	641	1500	○6400 K	<b>2660</b>
30	750	2000	○4000 K	<b>2575</b>
30	750	2000	○6400 K	<b>2661</b>

T16 (FD). Tubes miniatures.

T5		G5 Ø16 230V 6 000 h		
P (w)	L (mm)	Lumens	Teinte	Code
4	136	140	●3500 K	<b>0850</b>
6	212	280	●3000 K	<b>0853</b>
6	212	280	○4000 K	<b>2665</b>
6	212	280	○6500 K	<b>2662</b>
8	288	400	●3000 K	<b>0854</b>
8	288	400	○4000 K	<b>2666</b>
8	288	400	○6500 K	<b>2663</b>
13	517	850	●3000 K	<b>0855</b>
13	517	850	○4000 K	<b>2667</b>
13	517	850	○6500 K	<b>2664</b>

## TUBE FLUORESCENT T5

T16 (FDH). Tubes **HE** - haute efficacité - 100 Lumens/Watt.

T5		IRC 85 G5 Ø16 230V 24 000 h		
P (w)	L (mm)	Lumens	Teinte	Code
14	549	1200	●3000 K	<b>2861</b>
14	549	1200	○4000 K	<b>2862</b>
21	849	1900	●3000 K	<b>2863</b>
21	849	1900	○4000 K	<b>2668</b>
21	849	1750	○6500 K	<b>2627</b>
28	1149	2600	●3000 K	<b>2864</b>
28	1149	2600	○4000 K	<b>2669</b>
28	1149	2400	○6500 K	<b>2628</b>
35	1445	3300	●3000 K	<b>2865</b>
35	1445	3300	○4000 K	<b>2626</b>

T16 (FDHS). Tubes **HO** - flux lumineux élevé - 80 Lumens/Watt.

T5		IRC 85 G5 Ø16 230V 24 000 h		
P (w)	L (mm)	Lumens	Teinte	Code
24	549	1750	●3000 K	<b>2587</b>
24	549	1750	○4000 K	<b>2588</b>
39	849	3100	●3000 K	<b>2866</b>
39	849	3100	○4000 K	<b>2589</b>
54	1149	4450	●3000 K	<b>2867</b>
54	1149	4450	○4000 K	<b>2590</b>