



	1 ... 2,5 mm <sup>2</sup> 1 ... 2,5 MM <sup>2</sup> م <sup>2</sup> 2.5...1	- 5 ... + 50°C от-5°C До+ 50°C 50° +... 5 - درجة مئوية	- 5 ... + 50°C от-10°C До+ 60°C 60° +... 10 - درجة مئوية	40 mm 40 mm мм 40	25 s...15 min 25 с...15 МИН 25دقيقة 15...ثانية	<b>P</b> Мощность	< 0,6W < 0,6Вт وات 0.6 >	230V 50/60Hz 230В 50/60Гц هرتز 60/50 فلت 230		
	1 ... 2,5 mm <sup>2</sup> 1 ... 2,5 MM <sup>2</sup> م <sup>2</sup> 2.5...1									

2x 1A cos φ = 1 / 250 V~ 2x 1A cos φ = 1 / 250 B~ ~فولت 250 / 2x 1A cos φ 1	250 W 250 Вт واط 250	250 W 250 Вт واط 250	2x 58 W 14μF 2x 58 Вт 14 мкФ 2x فولت 14 ميكروفاراد 58	250 W 250 Вт واط 250	100 W 100 Вт واط 100	250 VA 250 ВА فولت أمبير 250	250 VA 250 ВА فولت أمبير 250	250 VA 250 ВА فولت أمبير 250



