

## Features

Use: Indoor  
Type of installation: SUSPENDED, CEILING MOUNTED  
Emission: DIRECT  
Optics: OPAL  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: Autonomy 1h/Recharge time 12h  
L: 2400mm  
A: 38mm  
H: 65mm  
Made in: ITALY  
Warranty: 5 years except battery  
Weight: 4.1kg

## Tech data

Luminaire input power: 39.1W  
Luminaire luminous flux: 3438lm  
Luminous flux in emergency: 11%  
IP: 40  
Insulation class: I  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 35W  
Source luminous flux: 5967lm  
Colour temperature: 4000K  
CRI: >80  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-22

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)



## SCREENS

---



LUCKY MINI: DIFF. OPALE PER L2400

103506.99




LUCKY MINI: DIFF. OPALE L=6500

103507.99


## COMPLETION ACCESSORIES

---



LUCKY MINI: COPPIA TESTATE BIA

103509.01



KIT GIUNZIONE MODULI P-30/LUCKY MINI

103317.99


## MOUNTING ACCESSORIES

---



LUCKY MINI: CAVO DI SOSPENSIONE L=3000

103513.99



KIT ALIMENTAZIONE L1200 3P BIA

108919.01

# LUCKY MINI

103523.01


novalux

ITALIAN LIGHTING DESIGN SINCE 1948



KIT ALIMENTAZIONE L3000 3P BIA

108920.01



KIT ALIMENTAZIONE L1200 5P BIA

108921.01



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.