




## Surface & Suspended specification sheet



01604 495 151  
collingwoodlighting.com

-  collingwoodled
-  /collingwoodlighting
-  collingwoodlighting

# Nova CSP

Designer light that can be suspended, surface or wall mounted

### Features

<b>IK rating</b>	IK06
<b>IP rating</b>	IP40
<b>CSP Switchable</b>	CCT Switchable
<b>UGR</b>	<19
<b>Sensor Option</b>	On Request
<b>Dimmable Option</b>	Yes (DALI-2, 1-10V, PUSH-DIM)
<b>LED Lifetime</b>	50,000h L70
<b>Emergency Option</b>	Yes, remotely using Salvus Route

### Installation information

<b>Install Connector Type</b>	Push-fit terminals 0,5 - 1,5mm <sup>2</sup>
<b>Inrush Current</b>	4.9A 154s
<b>Construction Material</b>	Aluminium housing, Microprism lens
<b>Weight</b>	3.8kg
<b>Maximum Ambient Temperature</b>	-20 to +50
<b>Electric Class (1, 2, 3)</b>	2

### Photometrics @ 25°C

	Finish	Feature l	W	Colour	Beam	lm	lm/W
NVB45DS	Black-Gold	450mm	26W	2700K	120°	2600	100
NVB45DS	Black-Gold	450mm	26W	3000K	120°	2800	108
NVB45DS	Black-Gold	450mm	26W	4000K	120°	3000	115
NVB60DS	Black-Gold	600mm	40W	2700K	120°	4200	117
NVB60DS	Black-Gold	600mm	40W	3000K	120°	4500	125
NVB60DS	Black-Gold	600mm	40W	4000K	120°	4800	133
NVB90DS	Black-Gold	900mm	68W	2700K	120°	7900	122
NVB90DS	Black-Gold	900mm	68W	3000K	120°	8300	128
NVB90DS	Black-Gold	900mm	68W	4000K	120°	9000	138
NVW45DS	White-Gold	450mm	26W	2700K	120°	2600	108
NVW45DS	White-Gold	450mm	26W	3000K	120°	2800	117
NVW45DS	White-Gold	450mm	26W	4000K	120°	3000	125
NVW60DS	White-Gold	600mm	40W	2700K	120°	4200	117
NVW60DS	White-Gold	600mm	40W	3000K	120°	4500	125
NVW60DS	White-Gold	600mm	40W	4000K	120°	4800	133
NVW90DS	White-Gold	900mm	68W	2700K	120°	7900	122
NVW90DS	White-Gold	900mm	68W	3000K	120°	8300	128
NVW90DS	White-Gold	900mm	68W	4000K	120°	9000	138

### Accessories

<b>NV45UPM</b>	Nova Uplight Kit, 450mm, 13W 1100lm, On-Off, 3000K	Sold Separately
<b>NV60UPM</b>	Nova Uplight Kit, 600mm, 20W 1700lm, On-Off, 3000K	Sold Separately
<b>NV90UPM</b>	Nova Uplight Kit, 900mm, 28W 2400lm, On-Off, 3000K	Sold Separately
<b>NVBSUS2M</b>	Nova Pendant Kit Black, 2 metres, 5 core cable	Sold Separately
<b>NVWSUS2M</b>	Nova Pendant Kit White, 2 metres, 5 core cable	Sold Separately
<b>EMRBST</b>	Salvus Route Black, Self Test, Open Corridor Lens	Sold Separately
<b>EMRWST</b>	Salvus Route White, Self Test, Open Corridor Lens	Sold Separately

### Guarantee

5 years (product), 2 years (on-site)

### Features & benefits

Colour switchable between 2700k, 3000k, & 4000k

Energy efficient up to 138lm/W

Available with DALI-2, 1-10V & PUSH-DIM

Wide light emitting surface designed for superior optical control and comfortable light

Makes rooms appear larger and wider

Floating impression when surface-mounted

Design-led pendant can be centrepiece of any room

Wall mounted creates interest

450mm and 600mm can be wall mounted

4000K for focus scenes - 3000K for social scenes - 2700K for relaxation

Light source energy efficiency:



Beam angle: 120°

