

PRODUCT-DETAILS

6747 AGM-201-500

Movement Detector MasterLINE brown



Informations générales

Extension du type de produit	6747 AGM-201-500
Code de produit	2CKA006700A0038
EAN	4011395175910
Description courte	Movement Detector MasterLINE brown

Description longue	<p>Wireless movement detector for detecting thermal motion. With display for detection and status indication. With ground and rear-field detection. With high-quality lens for optimum detection. Surveillance density: 84 sectors with 336 switching segments. With integrated dismantling protection. All functions controlled by microprocessor. With automatic range stabilization. With automatic interference suppression. With automatic dazzle-proofing. With automatic battery monitoring. Battery service life: typically 5 years, therefore practically maintenance-free. With brightness-independent test mode for evaluating the detection zone. Individual adjustment of detection range via enclosed protective foil which can be cut to size. Combinable with switch actuator WaveLINE, 1gang, with extension unit 6701-101. For standalone and group operation. Switch-off delay: 3 min. (single mode), individually adjustable at actuator (group mode). Send frequency: 868 MHz. Free-field range: approx. 100 m.</p>
--------------------	--

Installation

Instructions et manuels	DEBJE-0073-1-8061
-------------------------	-------------------

Technique

Fiche produit, informations techniques	No document needed
Tension nominale (U _r)	4.5 V
Auxiliary Voltage AC/DC	4.5 V AC/DC
Type de tension	DC
Plage de mesure	32 m
Nombre de sorties	1
Number of Switching Zones	1
Conception	MasterLINE
Product Range	WaveLINE
Minimum Switching Time	Switch-On 60 second [unit of time]
Type de raccordement	Cable Clamp
Type de montage	Surface Mounted
Sensor Type	Passive infrared
Finition de surface	Surface protection: Untreated Surface finishing: Matt
Matériau	Thermoplastic
Type d'encastrement	Wall mounted installation
Flux lumineux	0 ... 1000 lx
Model Number	Movement sensor
RAL Number	RAL 8017 - Brun chocolat
Couleur	brown
Composition chimique de la batterie	Lithium
Désignation des dimensions	FR03
Type de batterie	Portable
Poids de la batterie	11 g
Nombre de batteries	1
Application Function	Electrical Load and Light Control

Environnement

Température de l'air ambiant	Operation -25 ... +55 °C
Indice de protection	IP55
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CKA200000E6195
REACH Declaration	2CKA309999E9999
SCIP	83be1b14-9ff9-4043-86f7-11305175dabb Germany (DE)
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Produit Largeur Net	125 mm
Produit Hauteur Net	115 mm
Produit Longueur Net	141 mm
Poids net	0.54 kg

Commande

ID du produit remplacé	6700-0-0038
------------------------	-------------

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CKA100000E1779
-----------------------------------	-----------------

Classifications

ETIM 8	EC000138 - Sensor element for movement sensor
ETIM 9	EC000133 - Movement sensor/presence detector complete
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 50 80
eClass	V11.0 : 27144007

Accessories

Identifiant	Description	Type	Quantity	Unit Of Measure
2CKA006700A0023	WaveLine Flush Mounted Inserts 1 gang(s) 230 V	6702-500	1	piece
2CKA006770A0002	Flush Mounted Inserts	6770-500	1	piece

Catégories

Produits basse tension → Wiring Accessories - StandAlone Electronics → Outdoor Movement Detector → Professional Series

