

## Features

Use: Indoor  
Type of installation: SUSPENDED, CEILING MOUNTED  
Emission: DIRECT  
Optics: OPAL  
Colour: CAPPUCCINO  
Dimming: PUSH, DALI  
Emergency: NO  
L: 823x823mm  
A: 38mm  
H: 65mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 3kg

## Tech data

Luminaire input power: 27.3W  
Luminaire luminous flux: 2229lm  
IP: 40  
Insulation class: I  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 23W  
Source luminous flux: 3868lm  
Colour temperature: 3000K  
CRI: >80  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)

## SCREENS

---



LUCKY MINI: DIFF. OPALE L=6500

103507.99


## COMPLETION ACCESSORIES

---



LUCKY MINI: COPPIA TESTATE CAPPUCINO

103509.21




4x

KIT GIUNZIONE MODULI P-30/LUCKY MINI

103317.99


## MOUNTING ACCESSORIES

---



KIT ALIMENTAZIONE L1200 5P CAP

108921.21



KIT ALIMENTAZIONE L3000 5P CAP

108922.21



LUCKY MINI: CAVO DI SOSPENSIONE L=3000

103513.99