

## Features

Use: Indoor  
 Type of installation: RECESSED INTO PLASTERBOARD  
 Emission: DIRECT  
 Optics: SPOT  
 Beam: 36°  
 Colour: WHITE  
 Dimming: WITH ACCESSORY  
 Emergency: WITH ACCESSORY  
 L: 75mm  
 A: 75mm  
 H: 92mm  
 Warranty: 5 years  
 Weight: 0.385kg

## Tech data

Luminaire luminous flux: 908lm  
 Luminous flux in emergency: 1h: 44% / 3h: 18  
 IP: 54  
 Insulation class: III  
 Supply voltage: DC 500 mA  
 SELV: Si

## Source

Light source: LED  
 Source power: 10W  
 Colour temperature: 3000K  
 CRI: >90  
 LED lifespan: 30000h L70 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

## Standards


Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)



## ELECTRICAL ACCESSORIES

---




ALIM. LED MAX 18W 500MA

**101325.99**

## DIMMABLE ACCESSORIES

---




ALIM. LED 25W 500MA/2-50V DALI/PUSH

**101334.99**


## EMERGENCY ACCESSORIES

---



KIT EMERGENZA 1H 10V-54V

**18004.99**



KIT EMERGENZA 3H 10V-54V

**18005.99**