

**STRONGHOLD™**

## Metal Strapping System

Mechanical fastening applications demand high quality systems that can withstand harsh environments while maintaining a safe and secure physical infrastructure. Severe weather, intense UV rays, high vibration, and galvanic corrosion are all variables that can sacrifice performance and create safety hazards. Panduit offers innovative solutions that provide reliable fastening of critical components which allows businesses to minimize risk and enhance productivity.

The StrongHold™ Metal Strapping System is available in 316L stainless steel to deliver high performance, strength, and reliability, ideal for the Sign and Signal, Oil and Gas, and Industrial markets. Designed to work together in extreme conditions, the StrongHold™ metal strapping, buckles, and installation tool provide secure connections while offering lower installed costs. This system is part of the complete range of harsh environment solutions.



**Oil and Gas**



**Mining and Minerals**



**Sign and Signal**




**Wastewater Treatment**



**Shipbuilding**



**Food and Beverage**




**Installation Tool**



**Type L Buckle**



**Type E Buckle**



**Coated Strapping**



**Uncoated Strapping**

Part Number	Material	Length	Strap Breaking Strength	Min Bundle Diameter	Width	Thickness	Recommended Installation Tool	Std. Pkg. Qty.
		M	N	mm	mm	mm		
<b>StrongHold™ Metal Strapping (Uncoated) - Coil</b>								
IMS9.5T35-QR6L	Stainless Steel Type 316L	25	1780	26	9.5	0.35	BT75SDT	1
IMS12T35-QR6L	Stainless Steel Type 316L	25	2445	26	12	0.35	BT75SDT	1
IMS16T35-QR6L	Stainless Steel Type 316L	25	3110	26	16	0.35	BT75SDT	1
IMS19T75-QR6L	Stainless Steel Type 316L	25	4225	26	19	0.75	BT75SDT	1
<b>StrongHold™ Metal Strapping (Coated with Epoxy Polyester) - Coil</b>								
IMSP9.5T35-QR6L	Stainless Steel Type 316L	25	1780	26	9.5	0.35 <sup>^</sup>	BT75SDT	1
IMSP12T35-QR6L	Stainless Steel Type 316L	25	2445	26	12	0.35 <sup>^</sup>	BT75SDT	1
IMSP16T35-QR6L	Stainless Steel Type 316L	25	3110	26	16	0.35 <sup>^</sup>	BT75SDT	1

<sup>^</sup>Base material less coating

Part Number	Material	Width	Part Description	Std. Pkg. Qty.
		mm		
<b>StrongHold™ Buckles</b>				
IMSBL9.5-C6L	Stainless Steel Type 316L	9.5	Individual Buckle Style L for use with 9.5 mm strapping	100
IMSBL12-C6L	Stainless Steel Type 316L	12	Individual Buckle Style L for use with 12 mm strapping	100
IMSBL16-C6L	Stainless Steel Type 316L	16	Individual Buckle Style L for use with 16 mm strapping	100
IMSBE19-C6L	Stainless Steel Type 316L	19	Individual Buckle Style E for use with 19 mm strapping	100

**WORLDWIDE SUBSIDIARIES AND SALES OFFICES**

PANDUIT US/CANADA  
Phone: 800.777.3300

PANDUIT EUROPE LTD.  
London, UK  
cs-emea@panduit.com  
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.  
Republic of Singapore  
cs-ap@panduit.com  
Phone: 65.6305.7575

PANDUIT JAPAN  
Tokyo, Japan  
cs-japan@panduit.com  
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA  
Guadalajara, Mexico  
cs-la@panduit.com  
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.  
Victoria, Australia  
cs-aus@panduit.com  
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to [www.panduit.com/warranty](http://www.panduit.com/warranty)



**For more information**  
**Visit us at [www.panduit.com](http://www.panduit.com)**  
Contact Customer Service by email: [cs@panduit.com](mailto:cs@panduit.com)  
or by phone: 800.777.3300

©2017 Panduit Corp.  
ALL RIGHTS RESERVED.  
SSCB36--SA-ENG  
Replaces SSCB32  
11/2017