

Fusibles basse tension



ep.mersen.com

Cylindriques gG 10,3 x 38

Cylindriques aM 10,3 x 38

INT. (A)	TENS. (-)	CAT. NUMBER SANS VOYANT	REF. NUMBER SANS VOYANT	CAT. NUMBER AVEC VOYANT	REF. NUMBER AVEC VOYANT
0,5	500	FR10GG50V0,5	C211027J	-	-
1	500	FR10GG50V1	B212061J	-	-
2	500	FR10GG50V2	D213098J	FR10GG50V2I	S216653J
4	500	FR10GG50V4	X213598J	FR10GG50V4I	E217170J
6	500	FR10GG50V6	K215128J	FR10GG50V6I	T218195J
8	500	FR10GG50V10	D217169J	FR10GG50V8I	V219231J
10	500	FR10GG50V10	S218194J	FR10GG50V10I	E222207J
12	500	FR10GG50V12	W219761J	FR10GG50V12I	H200751J
16	500	FR10GG50V16	G200750J	FR10GG50V16I	H201809J
20	500	FR10GG50V20	D211028J	FR10GG50V20I	X211551J
25	500	FR10GG50V25	E213099J	FR10GG50V25I	W212585J
32	400	FR10GG40V32	A214107J	FR10GG40V32I	Z213600J
Neutre	-	FRN1038	R211569J	FRN1038	R211569J

Conditionnement : 10 pièces.

INT. (A)	TENS. (-)	CAT. NUMBER SANS INDICAT.	REF. NUMBER SANS INDICAT.	CAT. NUMBER AVEC VOYANT	REF. NUMBER AVEC VOYANT
0,5	500	FR10AM50V0,5	W216150J	-	-
1	500	FR10AM50V1	F217171J	FR10AM50V1I	X219233J
2	500	FR10AM50V2	H218714J	FR10AM50V2I	G222209J
4	500	FR10AM50V4	W219232J	FR10AM50V4I	K200753J
6	500	FR10AM50V6	F222208J	FR10AM50V6I	K201811J
8	500	FR10AM50V8	Z201295J	FR10AM50V8I	Z211553J
10	500	FR10AM50V10	Y211552J	FR10AM50V10I	H213102J
12	500	FR10AM50V12	A213601J	FR10AM50V12I	D214110J
16	500	FR10AM50V16	F214618J	FR10AM50V16I	P215132J
20	500	FR10AM50V20	X216151J	FR10AM50V20I	V216655J
25	400	FR10AM40V25	G217172J	FR10AM40V25I	L217682J
32	400	FR10AM40V32	J218715J	-	-
Neutre	-	FRN1038	R211569J	FRN1038	R211569J

Conditionnement : 10 pièces.

Cylindriques gG 14 x 51

Cylindriques aM 14 x 51

INT. (A)	TENS. (-)	CAT. NUMBER SANS PERCUT.	REF. NUMBER SANS PERCUT.	CAT. NUMBER À PERCUTEUR	REF. NUMBER À PERCUTEUR
10	690	FR14GG69V10	L200754J	FR14GG50V10P	Z216153J
16	690	FR14GG69V16	A211554J	FR14GG50V16P	Z218200J
20	690	FR14GG69V20	Z212588J	FR14GG50V20P	B219237J
25	690	FR14GG69V25	C213603J	FR14GG50V25P	L222213J
32	500	FR14GG50V32	W216656J	FR14GG50V32P	P200757J
40	500	FR14GG50V40	X218198J	FR14GG50V40P	P201815J
50	500	FR14GG50V50	Z219235J	FR14GG50V50P	D211557J
Neutre	-	FRN1451	M212600J	FRN1451	M212600J

Conditionnement : 10 pièces. Calibres 10A, 16A, 20A, 25A à perceur : 500V au lieu de 690V.

INT. (A)	TENS. (-)	CAT. NUMBER SANS PERCUT.	REF. NUMBER SANS PERCUT.	CAT. NUMBER À PERCUTEUR	REF. NUMBER À PERCUTEUR
10	690	FR14AM69V10	Z216659J	FR14AM50V10P	S200760J
16	690	FR14AM69V16	Q217686J	FR14AM50V16P	G211560J
20	690	FR14AM69V20	P218720J	FR14AM50V20P	E212593J
25	690	FR14AM69V25	E219769J	FR14AM50V25P	H213608J
32	500	FR14AM50V32	M222214J	FR14AM50V32P	N214625J
40	500	FR14AM50V40	Q200758J	FR14AM50V40P	X215645J
50	500	FR14AM50V50	E211558J	FR14AM50V50P	D218204J
Neutre	-	FRN1451	M212600J	FRN1451	M212600J

Conditionnement : 10 pièces. Calibres 10A, 16A, 20A, 25A à perceur : 500V au lieu de 690V.

Cylindriques gG 22 x 58

Cylindriques aM 22 x 58

INT. (A)	TENS. (-)	CAT. NUMBER SANS PERCUT.	REF. NUMBER SANS PERCUT.	CAT. NUMBER À PERCUTEUR	REF. NUMBER À PERCUTEUR
32	690	FR22GG69V32	F212594J	FR22GG69V32P	S211041J
40	690	FR22GG69V40	J213609J	FR22GG69V40P	R212075J
50	690	FR22GG69V50	P214626J	FR22GG69V50P	M213612J
63	690	FR22GG69V63	Y216646J	FR22GG69V63P	T1022160J
80	690	FR22GG69V80	Q217180J	FR22GG69V80P	Z1022165J
100	500	FR22GG50V100	E218205J	FR22GG50V100P	T217183J
125	500	FR22GG50V125	J219773J	FR22GG50V125P	H218208J
Neutre	-	FRN2258	R213616J	FRN2258	R213616J

Conditionnement : 10 pièces. Calibres 63A, 80A à perceur : 500V au lieu de 690V.

INT. (A)	TENS. (-)	CAT. NUMBER SANS PERCUT.	REF. NUMBER SANS PERCUT.	CAT. NUMBER À PERCUTEUR	REF. NUMBER À PERCUTEUR
32	690	FR22AM69V32	V213113J	FR22AM69V32P	X214633J
40	690	FR22AM69V40	N213613J	FR22AM69V40P	F215653J
50	690	FR22AM69V50	R214122J	FR22AM69V50P	K216669J
63	690	FR22AM69V63	C215650J	FR22AM50V63P	B217696J
80	690	FR22AM69V80	H216667J	FR22AM50V80P	Z218729J
100	500	FR22AM50V100	Y217693J	FR22AM50V100P	T222979J
125	500	FR22AM50V125	J218209J	FR22AM50V125P	S201312J
Neutre	-	FRN2258	R213616J	FRN2258	R213616J

Conditionnement : 10 pièces. Calibres 63A, 80A à perceur : 500V au lieu de 690V.

À couteaux gG tailles 00 - 0 - 1

À couteaux aM tailles 00 - 0 - 1

TAILLE	INTENS. (A)	TENS. (-)	COND.	CAT. NUMBER SANS VOYANT	REF. NUMBER SANS VOYANT
000/00C	63	500	9	NH00GG50V63	E213996H
000/00C	80	500	9	NH00GG50V80	Y216543H
000/00C	100	500	9	NH00GG50V100	B219122H
00	125	500	3	NH00GG50V125	R201863C
00	160	500	3	NH00GG50V160	P211084C
00	Neutre	-	10	NH00KNIFESGP	W216058J
0	125	500	3	NH0GG50V125	P222492C
0	160	500	3	NH0GG50V160	F223013C
0	200	500	3	NH0GG50V200	C229611C
0	Neutre	-	10	NH0NEUTRAL	Z219304J
1	160	500	3	NH1GG50V160	A218247C
1	200	500	3	NH1GG50V200	P218766C
1	250	500	3	NH1GG50V250	E219815C
1	Neutre	-	5	NH1NEUTRAL	A219834E

Cette gamme est disponible également en autres tailles, autres calibres avec perceur.

TAILLE	INTENS. (A)	TENS. (-)	COND.	CAT. NUMBER SANS VOYANT	REF. NUMBER SANS VOYANT
000	63	500	3	NH000AM50V63	X232504C
000	80	500	3	NH000AM50V80	C227863C
00	100	500	3	NH00AM50V100	Y232505C
00	125	500	3	NH00AM50V125	Z232506C
00	Neutre	-	10	NH00DKNIFESGP	W216058J
0	100	500	3	NH0AM50V100	A232507C
0	125	500	3	NH0AM50V125	B232508C
0	160	500	3	NH0AM50V160	C232509C
0	200	500	3	NH0AM50V200	A227884C
0	Neutre	-	10	NH0NEUTRAL	Z219304J
1	200	500	3	NH1AM50V200	G232513C
1	250	500	3	NH1AM50V250	J232515C
1	Neutre	-	5	NH1NEUTRAL	A219834E

Cette gamme est disponible également en autres tailles, autres calibres avec perceur.