


## PUSHBUTTON ACTUATOR, SPRING RETURN, WITH SYMBOL Ø22MM PLATINUM SERIES METAL, FLUSH, STOP/RED



Product designation				Pushbutton actuators, spring return, with symbol
Product type designation				LPSB11
General characteristics	3			
Colour				Red
Type of positions				Flush pushbutton
Material				Aluminium and zinc alloy
IEC degree of protecti	on			IP66, IP67 and IP69K
Mechanical features				
Operating force			kg-lb	<0.5Kg / 1.1lb
Mechanical life			cycles	5000000
Fixing				Without mounting adapter
Mounting adapter				LPXAU120M
UL technical data				
UL degree of protection				Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			
		min	°C	-40
Dimensions		max	°C	+85
Dimensions				



#### Certifications and compliance

_				
Com		l: _		
1.717	ורזו	112	111'L	

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1 UL508

## Certificates

cULus

#### ETIM classification



# LPSB1134

PUSHBUTTON ACTUATOR, SPRING RETURN, WITH SYMBOL Ø22MM PLATINUM SERIES METAL, FLUSH, STOP/RED

ETIM 8.0

EC000221 -Front element for push button