

PRODUCT-DETAILS

PS833889

PS833889 POLYSAFE ENCL. IP54

1250X1000X320 1DOOR



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | PS833889 |
| Code de produit | 4TBP833889C0100 |
| EAN | 5411815254277 |
| Description courte | PS833889 POLYSAFE ENCL. IP54 1250X1000X320 1DOOR |
| Description longue | Cabinets with window door are delivered assembled. The cabinets are made of self-extinguishing, glass-fibre reinforced and halogen-free polyester, coloured in RAL 7035 (light grey) and offer maximum protection for the operator and the built-in equipment by means of protective insulation and also a high degree of protection of IP54 in accordance with IEC 60529, EN 60529. The cabinets have a degree of protection of IK 07 according to EN 62262 and IEC 62262. Wall, floor, base and pole mounting. Combinable in height, width and depth. Rated insulation voltage $U_i = 1000V$ PSS5404 Cabinet 1250x1000x320 with one continuous door IP54, IK07 |

Technique

| | |
|-----------------------------|--------|
| Number of Flange Openings | 0 |
| Number of Conduit Inlets | 0 |
| Number of Rows | 0 |
| Cover Plate Type | Door |
| Classe de protection (NEMA) | Type12 |

| | |
|---------------------|-----------------------|
| Type de montage | Floor installation |
| Door Type | Single |
| Finition de surface | Untreated |
| Qualité du matériau | Plastic |
| Style de cache | Closed |
| RAL Number | RAL 7035 - Gris clair |
| Couleur | Grey |

Environnement

| | |
|---|--|
| Indice de protection | IP54 |
| Classe de protection | Isolated (Class II) |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS | 9AJK000580 |
| REACH Declaration | 9AJK000617 |
| SCIP | 32f455a8-ac40-4c05-b4e8-dfedc2dfc30d Belgium (BE) |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Dimensions

| | |
|---|---------------------------------------|
| Width in Number of Modular Spacings | 0 |
| Produit Largeur Net | 1000 mm |
| Produit Hauteur Net | 1250 mm |
| Produit Longueur Net | 320 mm |
| Poids net | 44 kg |
| Profondeur d'encastrement (t ₂) | 286 mm |
| Thickness | Cabinet Plate 4 mm Door Plate 4 mm |

Commande

| | |
|---------------------------|-------------|
| Emballage Niveau 1 Unités | box 1 pièce |
| Emballage Niveau 1 Poids | 46.4 kg |

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|------------|
| Déclaration de Conformité - CE | 9AJK000580 |
|--------------------------------|------------|

Installation

| | |
|-------------------------|--------------------|
| Instructions et manuels | No document needed |
|-------------------------|--------------------|

Downloads Préférés

Fiche produit, informations techniques

No document needed

Classifications

| | |
|----------------|---------------------------|
| ETIM 8 | EC000058 - Empty cabinet |
| ETIM 9 | EC000058 - Empty cabinet |
| Catégorie DEEE | Product Not in WEEE Scope |
| WEEE B2C / B2B | Business To Business |
| eClass | V11.0 : 27142408 |

Catégories

Produits basse tension → Tableaux, Coffrets et Armoires → Tableaux d'abonné encastrés IP40 → GRP cabinets → Polysafe

