

Microswitches for square body Protistor® fuse-links

ACCESSORIES FOR FUSES & FUSE SYSTEMS

MICROSWITCHES



- Remote signaling systems for fitting on Mersen fuses equipped with microswitch support:

All square-body sizes AC 44 / 8x / 9x / 12x / 17x / 20x / 30x and DC 7x / 12x / 17x / 30x / 60x

- Permanent indication of fuse state: conductive / blown
- Manual resetting
- Standard and low electrical level with different insulation levels
- Vapor and water tight type for use in corrosive atmosphere

MERSEN reserves the right to change, update or correct, without notice, any information contained in this datasheet.

Microswitches for square body Protistor® fuse-links

PRODUCT RANGE



MC3E1-5N

Insulation Voltage 1250VAC/VDC

Catalog number	Reference number	Rated voltage AC (IEC)	Rated voltage DC (IEC)	Rated current I _n	Rated impulse withstand voltage U _{imp}	Indication System	Weight	Package
MC3E1-5N	D310020	-	-	5 A	20 kV	Standard NO-NC	32 g	3
MC3E1-5N ETANCHE	L310027	1250 V	1250 V	3 A	16 kV	Watertight NO-NC IP50	32 g	3

Insulation Voltage 2200VAC/VDC

Catalog number	Reference number	Rated voltage AC (IEC)	Rated voltage DC (IEC)	Rated current I _n	Rated impulse withstand voltage U _{imp}	Indication System	Weight	Package
MCR3E1-5N ETANCHE	Q310031	2200 V	2200 V	3 A	30 kV	Watertight NO-NC IP50	59 g	1
MCR3E1-5N	G310023	2200 V	2200 V	5 A	30 kV	Standard NO-NC	60 g	1
MCR3E1-5NBS	P310030	2200 V	2200 V	3 A	30 kV	Low level NO-NC	58 g	1
MCR3E1-9NBS	H310024	2200 V	2200 V	3 A	30 kV	Double pole Low level NO-NC	67 g	1

MERSEN reserves the right to change, update or correct, without notice, any information contained in this datasheet.