




| Product designation | | | | Selector switch actuator key - 2 position |
|--------------------------|-----------------------|-----|--------|---|
| Product type designation | | | | LPFS32 |
| General characteristic | cs | | | |
| Colour | | | | Black |
| Type of positions | | | | Selector switch |
| Material | | | | Aluminium and zinc alloy |
| IEC degree of protection | | | | IP66, IP67 and IP69K |
| Mechanical features | | | | |
| Mechanical life | | | cycles | 1000000 |
| Fixing | | | | Without mounting adapter |
| Mounting adapter | | | | LPXAU120M |
| UL technical data | | | | |
| UL degree of protection | | | | Type1, 2, 3R, 4, 4X, 12, 12K |
| Ambient conditions | | | | |
| Temperature | | | | |
| | Operating temperature | | | |
| | | min | °C | -25 |
| | | max | °C | +70 |
| | Storage temperature | | | |
| | | min | °C | -40 |
| | | max | °C | +85 |
| Dimensions | | | | |



| K | ey |
|-----------------------|---------------------|
| Certifications and co | ompliance |
| Compliance | |
| | CSA C22.2 n° 14 |
| | IEC/EN/BS 60947-1 |
| | IEC/EN/BS 60947-5-1 |
| | UL508 |
| Certificates | |
| | cULus |
| ETIM classification | |
| | |

.50")



LPFS320R3433E SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 2 POSITION, 0 - 1 WITH DIFFERENT KEY CODE

ETIM 8.0

EC002611 -Control switch