


Corps aluminium blanc/Réflecteur à facettes.
Alimentation intégrée.

	1 LED	41 W	3500 lm
	230V	IP20	IK05 850° 30 000 h
Fixation	Faisceau	Teinte	Code
rail 1 allum. 029 (p.479)	36°	● 3000 K	50176
	36°	○ 4000 K	50177
	60°	● 3000 K	50172
	60°	○ 4000 K	50173
rail 3 allum. 023 (p.481)	36°	● 3000 K	50178
	36°	○ 4000 K	50179
	60°	● 3000 K	50174
	60°	○ 4000 K	50175



Corps aluminium noir/Réflecteur à facettes.
Alimentation intégrée.

Fixation	Faisceau	Teinte	Code
	rail 1 allum. 029 (p.479)	● 3000 K	50326
		○ 4000 K	50327
		● 3000 K	50322
		○ 4000 K	50323
	rail 3 allum. 023 (p.481)	● 3000 K	50328
		○ 4000 K	50329
		● 3000 K	50324
		○ 4000 K	50325

IKAR	3-4000K	41 W	36°
	h (m)	E _{max} (lx)	d (m)
	1	8036	0,65
	2	2009	1,3
	3	893	1,9
	4	502	2,6
	5	321	3,2

IKAR	3-4000K	41 W	60°
	h (m)	E _{max} (lx)	d (m)
	1	3688	1,15
	2	922	2,3
	3	410	3,5
	4	231	4,6
	5	148	5,8