

performances  
électriques

# grandes LONGUEURS



**Curant**

**PRÉFILCO vert 3422 300 m**

désignation	GAINE			haut. bas palette (m)	COURONNE				
	Ø ext. (mm)	référence	long. (m)		Ø ext. (mm)	Ø int. (mm)	larg. (mm)	Ø moyen int. (mm)	
20 ADSL	20	20080047	300	1800	1,92	920	570	320	560
20 TV 17VATCA	20	20080046	300	1800	1,92	920	570	320	560

**FLEXARAY+ bleu 400 à 700 m**

Ø ext. (mm)	STA	FTAP	GAINE			haut. bas palette (m)	COURONNE		
			référence	long. (m)	pal. (m)		Ø ext. (mm)	Ø int. (mm)	larg. (mm)
16	X		58101185	700	4200	1,95	1050	570	310
20	X		58101570	500	3000	1,94	1100	570	310
25	X		58101965	400	2400	1,98	1170	570	320
16	X		56101185	700	4200	1,95	1050	570	310
20	X		56101570	500	3000	1,94	1100	570	310
25	X		56101965	400	2400	1,98	1170	570	320

**ICTA gris 3422 120 à 1000 m**

Ø ext. (mm)	STA	FTAG	FTAP	GAINE			haut. bas palette (m)	COURONNE			
				référence	long. (m)	pal. (m)		Ø ext. (mm)	Ø int. (mm)	larg. (mm)	Ø moyen int. (mm)
16	X			11041185	700	4900	2,04	1030	580	270	575
16	X			11041195	1000	5000	1,90	1100	580	350	575
20	X			11041570	500	3500	2,04	1100	580	270	575
20	X			11041590	900	4500	2,05	1210	580	380	575
25	X			11041965	400	2400	2,19	1100	580	340	575
25	X			11041970	500	2500	1,85	1200	580	340	575
32	X			11042750	200	1200	2,03	1100	570	310	560
40	X			11043343	120	720	2,37	1090	570	370	560
16	X			10041185	700	4900	2,04	1050	570	310	575
20	X			10041570	500	3500	2,04	1100	570	310	575
25	X			10041965	400	2400	2,19	1170	570	320	575
32	X			10042750	200	1200	2,03	1100	570	310	560
25	X			100419650008	400	2400	2,19	1100	580	340	575

**ICA gris 3321 200 à 700 m**

Ø ext. (mm)	GAINE			haut. bas palette (m)	COURONNE			
	référence	long. (m)	pal. (m)		Ø ext. (mm)	Ø int. (mm)	larg. (mm)	Ø moyen int. (mm)
16	15041185	700	4200	1,95	1050	570	310	560
20	15041570	500	3000	1,95	1100	570	310	560
25	15041965	400	2400	1,85	1170	570	320	560
32	15042750	200	1200	2,05	900	570	300	560

**ICTA vert 3422 400 à 500 m**

Ø ext. (mm)	STA	FTAG	FTAP	GAINE			haut. bas palette (m)	COURONNE			
				référence	long. (m)	pal. (m)		Ø ext. (mm)	Ø int. (mm)	larg. (mm)	Ø moyen int. (mm)
20	X			11081570	500	3500	2,04	1100	580	270	575
20	X	X		10081570	500	3500	2,04	1100	570	310	575
25	X			11081965	400	2400	2,19	1170	570	320	575

**IRL TULIPE gris 3321 2 et 3 m**

Ø ext. (mm)	botte (m)	GAINE			L (mm)	FARDEAU	
		référence	long. (m)	pal. (m)		L (mm)	G (mm)
16	50	16041106	2	3000	1240	2000	450
16	75	16041108	3	4500	1240	3000	450
20	34	16041506	2	2040	1240	2000	460
20	51	16041508	3	3060	1240	3000	460
25	34	16041906	2	1360	1240	2000	460
25	51	16041908	3	2040	1240	3000	460
32	30	16042708	3	1080	1240	2000	450
40	21	16043308	3	795	1240	3000	450
50	15	16043308	3	540	1240	3000	470
63	9	16044308	3	324	1240	3000	470

**FLEXICHOC noir bandes grises 3522 120 à 200 m**

Ø ext. (mm)	STA	FTAG	FTAP	GAINE			haut. bas palette (m)	COURONNE			
				référence	long. (m)	pal. (m)		Ø ext. (mm)	Ø int. (mm)	larg. (mm)	Ø moyen int. (mm)
40	X			12023350	200	1000	1,95	1200	600	360	600
40	X			12023350008	200	1000	1,95	1200	600	360	600
50	X			12023945	150	750	2,20	1220	600	410	600
63	X			12024343	120	480	2,11	1270	600	490	600

**FACILOflex noir bandes blanches 200 m**

référence	GAINE			haut. bas palette (m)	COURONNE		
	long. (m)	pal. (m)	Ø ext. (mm)		Ø int. (mm)	larg. (mm)	Ø moyen int. (mm)
29021550	200	1200	1,95	900	560	300	560

