


	<h2>Product Environmental Profile</h2>	
---	--	---

	<h3>Connection Terminal: Convector Connector</h3>
---	---

Representative product	Convector connector with 1 entry Product category : Power connection accessories
Description of the product	EATON Capri offers convector terminals are to be used with flexible & rigid wires from 0.75 to 2.5 mm ² in the residential application. It has an option of 1 and 2 inputs in order to have optimal connections as per the requirement with 24A of maximum current intensity and are certified in accordance with EN60998-1 and EN60998-2-2 standards. These are offered in pot packaging.
Homogeneous Environmental Families Covered	The PEP concerns all the other product offerings covering convector type connection terminals as described below: <ol style="list-style-type: none"> 1. Convector connector with 2 entries
Functional unit	To connect together the power transmission cables for one packaging unit, under operating conditions identical to those of the cable, namely: 1 A during 30 years, with a use rate of 70%. Lifetime and use rate correspond to the residential building application as defined in the table given in Appendix 1 of the specific rules for Wire, Cables and Accessories.
Company information	Eaton Cooper Capri SAS 36, rue des Fontenils 41600, Nouan-le-Fuzelier, France Email: productstewardship-es@eaton.com

Constituent Materials			
Reference product mass	2.57E-03 kg (With packaging)		
Category PEP Material	Materials	Mass (kg)	Percentage (%)
Plastic	PA 66	1.40E-03	54.51%
Plastic	PET	4.35E-04	16.94%
Others	Cardboard	3.58E-04	13.94%
Metal	Stainless Steel	2.25E-04	8.76%
Metal	Copper	1.50E-04	5.84%
Metal	Tin	1.43E-07	<0.1%
Total		2.57E-03	100%

Substance Assessment

The representative product is compliant with the EU-RoHS Directive (2011/65/EU) by application of exemptions and the product contains lead (Pb) which is listed as Substance-of-Very-High-Concern (SVHC) on the Candidate List of the EU REACH Regulation (1907/2006/EC). However, the Lead concentration is below threshold as per the Article definition under the REACH Regulation.

Additional Environmental Information

Manufacturing	The reference product is manufactured at the direct source supplier plant in China which has set operational procedures for environmental protection and complies with local regulations.
Distribution	Eaton is committed to minimizing weight and volume of product and packaging with focus to optimize transport efficiency.
Installation	The installation of the product requires standard tools which do not require any additional energy source and no waste other than the obsolete product packaging is generated during this step.
Use	The product does not require maintenance during operation.
End of life	If product undergoes direct shredding, then the recyclability rate is 16.5% The rate is calculated based on the method of the IEC /TR 62635.

Environmental Impacts

The calculation of the environmental impacts is the result of the Product's Life Cycle Analysis in accordance with ISO 14040/44, covering the entire lifecycle, i.e. "Cradle-to-Grave" including the following life cycle phases: production, distribution, installation, use and end of life.

System modelling was carried out using the commercial LCA software EIME v5.9.4 with database version CODDE-2022-01.

Manufacturing Phase	The product is manufactured at direct source supplier in China. The packed product is then shipped to Eaton facility Eaton Neuan-Le-Fuzelier, France plant through 440km by lorry and 20,200km by container ship. Energy model used: China
----------------------------	---

Distribution Phase	Distribution of the product in its packaging from the Eaton's last logistics platform to the installation place in France is considered as per PCR rules.
Installation Phase	Product is installed in France. Only treatment of packaging waste is considered in this phase. Energy model used for treatment of packaging: Europe
Use Phase	<u>Reference lifetime:</u> 30 Years Usage rate: 70% of reference lifetime <u>Energy model used:</u> France <u>Usage profile:</u> Power loss with 1A current flow is 1.56E-05 W. The product is active for 70% of the time. Total energy losses are 2.87 Wh over the 30 years calculated at 1A current
End of life Phase	Product disposed with WEEE guidelines. Energy model used: Europe

Environmental Impact Indicators: Mandatory

Impact Indicators	Unit	Total	Manufacturing	Distribution	Installation	Use*(B6 Only)	End of life
Global warming (GWP100)	kg CO ₂ eq.	2.09E-02	2.01E-02	1.73E-04	1.05E-04	1.85E-04	3.80E-04
Ozone layer depletion	kg CFC-11 eq.	5.64E-10	5.48E-10	3.50E-13	2.63E-13	2.55E-12	1.33E-11
Acidification potential	kg SO ₂ eq.	7.91E-05	7.68E-05	7.77E-07	4.97E-07	5.40E-07	4.40E-07
Eutrophication	kg PO ₄ ³⁻ eq.	2.05E-05	1.99E-05	1.79E-07	1.22E-07	1.02E-07	1.54E-07
Photochemical oxidation	kg ethylene eq.	5.83E-06	5.66E-06	5.52E-08	3.59E-08	3.04E-08	4.82E-08
Abiotic depletion (elements)	kg antimony eq.	2.86E-07	2.86E-07	6.92E-12	4.27E-12	1.78E-10	4.15E-12
Abiotic depletion (fossil fuels)	MJ	2.00E-01	1.92E-01	2.43E-03	1.47E-03	2.71E-03	1.69E-03
Water Pollution	m ³	6.16E-01	5.44E-01	2.84E-02	1.72E-02	5.64E-03	2.12E-02
Air pollution	m ³	1.52E+00	1.47E+00	7.09E-03	5.01E-03	1.67E-02	1.86E-02

*B6 is energy requirements during the use stage. Other sub modules in the use stage (B1-B5, B7) are equal to zero. So, it is not listed in the table.

Environmental Impact Indicators: Optional

Impact Indicators	Unit	Total	Manufacturing	Distribution	Installation	Use*(B6 Only)	End of life
Use of renewable primary energy, excluding renewable primary energy resources used as raw materials	MJ	8.29E-03	4.89E-03	3.26E-06	2.52E-06	3.40E-03	2.32E-06
Use of renewable primary energy resources used as raw materials	MJ	9.66E-04	9.66E-04	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials)	MJ	9.26E-03	5.85E-03	3.26E-06	2.52E-06	3.40E-03	2.32E-06
Use of non-renewable primary energy, excluding non-renewable primary energy resources used as raw materials	MJ	2.09E-01	1.66E-01	2.44E-03	1.48E-03	3.68E-02	2.20E-03
Use of non-renewable primary energy resources used as raw materials	MJ	5.50E-02	5.50E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials)	MJ	2.64E-01	2.22E-01	2.44E-03	1.48E-03	3.68E-02	2.20E-03
Use of secondary materials	kg	6.36E-04	6.36E-04	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Net use of fresh water	m ³	8.22E-04	8.14E-04	1.55E-08	1.11E-08	7.79E-06	2.86E-07
Hazardous waste disposed of	kg	2.42E-02	2.09E-02	0.00E+00	9.25E-09	2.85E-06	3.26E-03
Non-hazardous waste disposed of	kg	9.85E-03	9.80E-03	6.14E-06	2.31E-05	1.84E-05	6.95E-06
Radioactive waste disposed of	kg	6.83E-07	6.56E-07	4.38E-09	3.28E-09	7.74E-09	1.22E-08
Materials for recycling	kg	7.39E-04	0.00E+00	0.00E+00	4.46E-04	0.00E+00	2.93E-04
Materials for energy recovery	kg	3.30E-04	0.00E+00	0.00E+00	3.30E-04	0.00E+00	0.00E+00
Total use of primary energy during the life cycle	MJ	2.74E-01	2.27E-01	2.45E-03	1.48E-03	4.02E-02	2.20E-03

*B6 is energy requirements during the use stage. Other sub modules in the use stage (B1-B5, B7) are equal to zero. So, it is not listed in the table.

The above results are with the following parameters:

- 1 convector connector for the production, distribution, installation and end of life stages
- 1 convector connector and 1A for the use stage

The potential impact of the use stage, estimated as Joule losses, shall be calculated by the user of the PEP as a function of the actual amperage during the use of the product by multiplying the impact considered by the square of the intensity. The PEP is valid within an intensity range taking into account of the maximum permissible intensity of 24A.


To evaluate the environmental impact of other product covered by this PEP, multiply the impact figures by-
PEP ecopassport® n° EATO-00053-V01.01-EN

Factors for Manufacturing, Distribution, Installation, Use and End-of-Life Phase:

Product	Phases	Global warming (Kg CO ₂ eq.)	Ozone depletion (kg CFC-11 eq.)	Acidification of soil and water (kg SO ₂ eq.)	Eutrophication (kg PO ₄ ³⁻ eq.)	Photochemical Ozone formation (kg ethylene eq.)	Depletion of abiotic resources - elements (kg Sb eq.)	Depletion of abiotic resources - fossil fuels (MJ)	Water pollution (m ³)	Air pollution (m ³)
Convector connector with 1 entry (reference product)	All Phases					1.00				
Convector connector with 2 entries	Manufacturing	1.12	1.49	1.12	1.10	1.12	1.54	1.12	1.14	1.21
	Distribution					1.12				
	Installation					1.00				
	Use					1.49				
	End of Life	1.14	1.16	1.16	1.15	1.17	1.17	1.17	1.15	1.17

Disclaimer

This Product Environmental Profile and its content is based on information available to us. It refers to the product at the date of issue. We make no express or implied representations or warranties with respect to the information contained herein.

<i>Registration N°</i>	EATO-00053-V01.01-EN	<i>Drafting rules</i>	PCR-ed3-EN-2015 04 02
<i>Verifier accreditation N°</i>	VH47	Supplemented by	PSR-0001-ed3-EN-2015 10 16
<i>Date of issue</i>	10-2022	<i>Information and reference documents</i>	www.pep-ecopassport.org
		<i>Validity period</i>	5 years
Independent verification of the declaration and data, in compliance with ISO 14025: 2010			
Internal	X	External	
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)			
<i>The elements of the present PEP cannot be compared with elements from another program.</i>			
<i>Document in compliance with ISO 14025: 2010 « Environmental labels and declarations. Type III environmental declarations »</i>			