

PRODUCT-DETAILS

N2241 CV

110° motion sensor - 2M - Champagne Movement sensor Champagne - Zenit



Informations générales

Extension du type de produit	N2241 CV
Code de produit	2CLA224100N1901
EAN	8427238092959
Description courte	110° motion sensor - 2M - Champagne Movement sensor Champagne - Zenit

Description longue	<p>Color: Champagne. Rated voltage: 127 - 230 Vac \pm 10% / 50 - 60 Hz Outputs: 1 Normally Open (NO). Potential free Max. power: - Incandescent: 1.800W @230Vac / 1.000W @127Vac - Halogen with electronic or ferromagnetic transformer: 750VA @230Vac / 400VA @127Vac - Fluorescent lamps or motors: 400VA @230Vac / 200VA @127Vac For automatic switching of devices dependent on motion and brightness. With integrated selector switch for ON-AUTOMATIC-OFF in the front side. Switch-off delay: 10 sec to 10 min or short-time pulse 1 sec adjustable (from the front side). Detection range: 5 m radius Adjustable light set point level for activation (from the front side). Detection angle: 110 ° Mounting height: 1,2 m Auxiliary control with N2X04.X push-buttons Temperature range (Device): -10 °C to 40 °C Size: 2 modules.</p>
--------------------	--

Installation

Instructions et manuels	2CLX224109N1001
-------------------------	-----------------

Technique

Fiche produit, informations techniques	9AKK10103A5108
Tension nominale (U _r)	230 V
Type de tension	AC
Current Range	Minimum 3 A Maximum 8 A
Maximum Control Current DC	1800 mA
Fréquence (f)	50...60 Hz
Maximum Switching Power	1800 W
Plage de mesure	Diameter Detection range on floor 5 m
Number of Switching Zones	3
Design Range	Zenit
Délai (T)	On 10 second [unit of time] Off 600 second [unit of time]
Minimum Switching Time	Switch-On 10 second [unit of time]
Type de raccordement	Screw
Type de montage	Flush Mounted
Sensor Type	Passive infrared
Finition de surface	Surface protection: Decor Surface finishing: Matt
Matériau	Material quality: Thermoplastic Material: Plastic
Flux lumineux	3...1000 lx
Model Number	Movement sensor
RAL Number	RAL 9010 - Blanc pur
Couleur	Champagne
Nombre de batteries	0
Application Function	Electrical Load and Light Control

Environnement

Température de l'air ambiant	Operation -5 ... +35 °C Storage -5 ... +50 °C
Indice de protection	IP20
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CLC224100N1901
REACH Declaration	9AKK108467A7464
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Produit Largeur Net	44 mm
Produit Hauteur Net	44 mm
Produit Longueur Net	40 mm
Poids net	0.108 kg
Profondeur d'encastrement (t ₂)	32 mm

Commande

ID du produit remplacé

2CLA224100N1902

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité
- CE

9AKK106930A2195

Classifications

ETIM 8	EC000133 - Movement sensor complete
ETIM 9	EC000133 - Movement sensor/presence detector complete
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85365080
UNSPSC	39122236

Catégories

Produits basse tension → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Electronic Controls

