

Speed controllers, 5.6 A, 2.2 kW, Sensor input 4, 180/207 V DC, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2, with manual override switch, with braking resistance, STO (Safe Torque Off)



**Part no. RASP5-5401A31-412R110S1
198829**

Product name	Eaton Moeller® series Rapid Link Speed controller
Part no.	RASP5-5401A31-412R110S1
EAN	4015081968879
Product Length/Depth	157 millimetre
Product height	270 millimetre
Product width	220 millimetre
Product weight	3.6 kilogram
Certifications	RoHS UL approval UL 61800-5-1 CE IEC/EN 61800-5-1
Product Tradename	Rapid Link
Product Type	Speed controller
Product Sub Type	None
Catalog Notes	3 fixed speeds and 1 potentiometer speed can be switched over from U/f to (vector) speed control Connection of supply voltage via adapter cable on round or flexible busbar junction Diagnostics and reset on device and via AS-Interface integrated PTC thermistor monitoring and Thermoclick with safe isolation optional: 4 sensor inputs with M12-Y adapter for switchover to creep speed optional: Faster stop if external 24 V fails Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation with AUTO - OFF/RESET - HAND key switches with selector switch REV - OFF - FWD
Features	Parameterization: Fieldbus Diagnostics and reset on device and via AS-Interface Parameterization: drivesConnect mobile (App) Parameterization: Keypad Parameterization: drivesConnect
Fitted with:	Key switch position AUTO PTC thermistor monitoring Braking resistance Key switch position OFF/RESET Manual override switch Selector switch (Positions: REV - OFF - FWD) Braking resistance Key switch position HAND IGBT inverter Thermo-click with safe isolation Control unit Internal DC link PC connection Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation
Functions	Brake chopper with braking resistance for dynamic braking For actuation of motors with mechanical brake 1 potentiometer speed 4-quadrant operation possible STO (Safe Torque Off) 3 fixed speeds
Degree of protection	NEMA 12 IP65
Electromagnetic compatibility	1st and 2nd environments (according to EN 61800-3)
Overvoltage category	III
Product category	Speed controller
Protocol	ASI AS-Interface profile cable: S-7.4 for 31 modules

Radio interference class		C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary. C1: for conducted emissions only
Rated impulse withstand voltage (Uimp)		2000 V
System configuration type		Phase-earthed AC supply systems are not permitted. Center-point earthed star network (TN-S network) AC voltage
Mounting position		Vertical
Shock resistance		15 g, Mechanical, According to IEC/EN 60068-2-27, 11 ms, Half-sinusoidal shock 11 ms, 1000 shocks per shaft
Vibration		Resistance: 6 Hz, Amplitude 0.15 mm Resistance: 10 - 150 Hz, Oscillation frequency Resistance: 57 Hz, Amplitude transition frequency on acceleration Resistance: According to IEC/EN 60068-2-6
Altitude		Above 1000 m with 1 % performance reduction per 100 m Max. 2000 m
Ambient operating temperature - min		-10 °C
Ambient operating temperature - max		40 °C
Ambient storage temperature - min		-40 °C
Ambient storage temperature - max		70 °C
Climatic proofing		In accordance with IEC/EN 50178 < 95 %, no condensation
Current limitation		Adjustable, motor, main circuit 0.5 - 5.6 A, motor, main circuit
Delay time		< 10 ms, Off-delay < 10 ms, On-delay
Efficiency		98 % (η)
Heat dissipation at current/speed		36.6 W at 25% current and 0% speed 38.1 W at 25% current and 50% speed 42 W at 50% current and 0% speed 42.5 W at 50% current and 90% speed 44.2 W at 50% current and 50% speed 55.9 W at 100% current and 0% speed 58.3 W at 100% current and 90% speed 60.4 W at 100% current and 50% speed
Input current ILN at 150% overload		5.3 A
Leakage current at ground IPE - max		3.5 mA
Mains current distortion		120 %
Mains switch-on frequency		Maximum of one time every 60 seconds
Mains voltage - max		480 V
Mains voltage - min		380 V
Mains voltage tolerance		380 - 480 V (-10 %/+10 %, at 50/60 Hz)
Operating mode		Sensorless vector control (SLV) BLDC motors U/f control PM and LSPM motors Synchronous reluctance motors
Output frequency - max		500 Hz
Output frequency - min		0 Hz
Overload current		For 60 s every 600 s At 40 °C
Overload current IL at 150% overload		8.4 A
Rated frequency - max		66 Hz
Rated frequency - min		45 Hz
Rated operational current (Ie)		5.6 A at 150% overload (at an operating frequency of 8 kHz and an ambient air temperature of +40 °C)
Rated operational power at 380/400 V, 50 Hz, 3-phase		2.2 kW
Rated operational voltage		400 V AC, 3-phase 480 V AC, 3-phase
Resolution		0.1 Hz (Frequency resolution, setpoint value)
Starting current - max		200 %, IH, max. starting current (High Overload), For 2 seconds every 20 seconds, Power section
Supply frequency		50/60 Hz

Switching frequency		8 kHz, 4 - 32 kHz adjustable, fPWM, Power section, Main circuit
Assigned motor power at 460/480 V, 60 Hz, 3-phase		3 HP
Braking current		≤ 0.6 A (max. 6 A for 120 ms), Actuator for external motor brake
Braking torque		≤ 30 % (I/Ie) Adjustable to 100 % (I/Ie), DC - Main circuit
Braking voltage		280/207 V DC -15 % / +10 %, Actuator for external motor brake
Switch-on threshold for the braking transistor		765 V DC
Rated conditional short-circuit current (Iq)		10 kA
Short-circuit protection (external output circuits)		Type 1 coordination via the power bus' feeder unit, Main circuit
Rated control voltage (Uc)		180/207 V DC (external brake 50/60 Hz) 24 V DC (-15 %/+20 %, external via AS-Interface® plug)
Communication interface		AS-Interface
Connection		Plug type: HAN Q4/2
Interfaces		Specification: S-7.4 (AS-Interface®) Max. total power consumption from AS-Interface® power supply unit (30 V): 190 mA Number of slave addresses: 31 (AS-Interface®)
Cable length		C1 ≤ 1 m, maximum motor cable length C3 ≤ 25 m, maximum motor cable length C2 ≤ 5 m, maximum motor cable length
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Frequency converter =< 1 kV (EC001857)		
Electric engineering, automation, process control engineering / Electrical drive / Static frequency converter / Static frequency converter = < 1 kV (ec@ss10.0.1-27-02-31-01 [AKE177014])		
Mains voltage	V	380 - 480
Mains frequency		50/60 Hz
Number of phases input		3
Number of phases output		3

Max. output frequency	Hz	500
Max. output voltage	V	500
Nominal output current I _{2N}	A	5.6
Max. output at quadratic load at rated output voltage	kW	2.2
Max. output at linear load at rated output voltage	kW	2.2
Relative symmetric net frequency tolerance	%	10
Relative symmetric net voltage tolerance	%	10
Number of analogue outputs		0
Number of analogue inputs		0
Number of digital outputs		0
Number of digital inputs		4
With control element		Yes
Application in industrial area permitted		Yes
Application in domestic- and commercial area permitted		Yes
Supporting protocol for TCP/IP		No
Supporting protocol for PROFIBUS		No
Supporting protocol for CAN		No
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		Yes
Supporting protocol for KNX		No
Supporting protocol for Modbus		No
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		No
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for BACnet		No
Supporting protocol for other bus systems		No
Number of HW-interfaces industrial Ethernet		0
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		0
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		1
Number of HW-interfaces serial TTY		0
Number of HW-interfaces USB		0
Number of HW-interfaces parallel		0
Number of HW-interfaces other		1
With optical interface		No
With PC connection		Yes
Integrated breaking resistance		Yes
4-quadrant operation possible		Yes
Type of converter		U converter
Degree of protection (IP)		IP65
Degree of protection (NEMA)		12
Height	mm	270
Width	mm	220

