




PANDUIT P/N	WEIGHT
P42B11M	7.4kg




REAR VIEW



TOP VIEW




FRONT VIEW




SIDE VIEW

NOTES:


- IDENTIFICATION:
 - UNIT TYPE: BASIC
 - ORIENTATION: VERTICAL, 0U FULL
 - OUTLET QTY&TYPE: (30) C13, (12) C19
 - BREAKER QTY&TYPE: (6) 16AMP, SINGLE-POLE
 - INPUT VOLTAGE: 200-240/346-415VAC, WYE
 - INPUT CURRENT: 32A
 - INPUT PHASE: THREE-PHASE WYE
 - RATED POWER: 22.0kVA
 - INPUT PLUG: IEC 60309 3P+N+E 6H 32A
 - INPUT CORD LENGTH: 3m [10']
- ACCESSORIES: POCKET GUIDE
- RoHS COMPLIANT
- VISIT PANDUIT'S ON-LINE CATALOG AT WWW.PANDUIT.COM FOR ADDITIONAL PRODUCT INFORMATION CONTAINED IN THE SPECIFICATION SHEET AS WELL AS A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART
- MAXIMUM ALLOWABLE INPUT POWER = 22.0 kW
- INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES



PLUG
32 AMP, 230/400V x 3~ WYE
4P/5W
IEC 60309, SPLASHPROOF, IP44
2P (S); 4T (W), 6H;



TWELVE (12)
RECEPTACLES
16 AMP, 250V
STRAIGHT BLADE
IEC 60320/C19



THIRTY (30)
RECEPTACLES
10 AMP, 250V
STRAIGHT BLADE
IEC 60320/C13

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
01B	08/21/2017	KUN	MIM	EDM	REVISED TOLERANCES	P42B11M
01A	06/28/2017	KUN	MIM	EDM	INITIAL RELEASE	P42B11M

WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATURE BOX. THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY		SIGN
		DATE
		PRINT
TITLE: BASIC SERIES PDU P42B11M CUSTOMER DRAWING		
ITEM REVISION NAME:		PANDUIT
DATASHEET FILE NAME:		
UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCE ARE: mm [IN]		MATERIAL/COLOR: N/A
Tolerance(mm) 04<L<50 ±0.5 50<L<250 ±1.0 250<L<500 ±1.5 500<L<1000 ±2.5 1000<L<2000 ±4.0		DRAWING NUMBER: P42B11M_DC
THIRD ANGLE PROJECTION	DRAWN BY: KUN DATE: 05/24/2017 CHK: SEAN SCALE: NONE	SHT 1 OF 1 SCALE: B