

PRODUCT-DETAILS

SBA-F-2.1.1-WL

SBA-F-2.1.1-WL WL-Sensor/Blind act. 2/1g



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | SBA-F-2.1.1-WL |
| Code de produit | 2CKA006200A0080 |
| EAN | 4011395215692 |
| Description courte | SBA-F-2.1.1-WL WL-Sensor/Blind act. 2/1g |
| Description longue | For controlling blind or awning motors. Communication with the free@home system is carried out wireless. With integrated blind actuator. Blind function is available also without prior programming (left sensor channel is pre-configured). Configuration can be changed later via the web interface (groups, scenes, etc.). The right sensor channel for programming additional functions (groups, scenes, etc.). For contacting 2gang rocker 6230-2x-xxx, 6231-2x-xxx, 6232-2x-xxx, 6233-2x-xxx and 6234-2x-xxx. 3 wire connection (neutral conductor required). With two 230 V extension unit inputs (Up/Down). With fixing claws. |

Installation

| | |
|-------------------------|--------------------|
| Instructions et manuels | No document needed |
|-------------------------|--------------------|

Technique

| | |
|--|-----------------|
| Fiche produit, informations techniques | 2CKA001473B9110 |
| Type de courant | AC |
| Tension nominale (U _r) | 230 V |
| Auxiliary Voltage AC/DC | 230 V AC/DC |

| | |
|---------------------------|---------------------------------|
| Courant nominal (I_n) | 4 A |
| Maximum Switching Current | Resistive Load 4 A |
| Fréquence assignée (f) | 50 ... 60 Hz |
| Maximum Switching Power | 920 W |
| Nombre de sorties | 2 |
| Compatible Bus Systems | free@home |
| Product Range | free@home |
| Type de charge | Operation mode Blind |
| Type de montage | Flush Mounted |
| Nombre de batteries | 0 |
| Application Function | Data Communication / Multimedia |

Environnement

| | |
|---|--|
| Température de l'air ambiant | Operation -5 ... +45 °C |
| Indice de protection | IP20 |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS | 2CKA200000E4797 |
| REACH Declaration | 2CKA309999E9999 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Dimensions

| | |
|-------------------------------------|---------|
| Produit Largeur Net | 71 mm |
| Produit Hauteur Net | 71 mm |
| Produit Longueur Net | 34 mm |
| Poids net | 104.2 g |
| Profondeur d'encastrement (t_2) | 32 mm |

Commande

| | |
|--------------------------------------|------------------------------------|
| ID Produit de remplacement (NOUVEAU) | 2CKA006400A0096 2CKA006200A0283 |
| ID du produit remplacé | 6200-0-0080 |

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|-----------------|
| Déclaration de Conformité - CE | 2CKA100000E2645 |
|--------------------------------|-----------------|

Classifications

| | |
|----------------|--|
| ETIM 8 | EC001330 - Shutting actuator for bus system |
| ETIM 9 | EC001330 - Shutting actuator for bus system |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |

CN8

8538 90 91

eClass

V11.0 : 27143128

Catégories

Produits basse tension → Home and Building Automation → free@home → Shading Control → Blind Actuators 230 V AC

