



Goulotte GBRs
(GBRS Trunking)

BP TRCC M6x12 HE



| Description | Code | Masse/Weight Kg/p | Ep./Th. mm | H mm | l./w. mm |
|-------------------|--------|----------------------|---------------|---------|-------------|
| CC GBRs 24x50 SZ | 518445 | 0,550 | 1,00 | 24,00 | 54 |
| CC GBRs 24x75 SZ | 518450 | 0,640 | 1,00 | 24,00 | 78 |
| CC GBRs 24x100 SZ | 518455 | 0,730 | 1,00 | 24,00 | 102 |
| CC GBRs 24x147 SZ | 518465 | 0,920 | 1,00 | 24,00 | 150 |
| CC GBRs 24x195 SZ | 518475 | 1,100 | 1,00 | 24,00 | 198 |

G : Pre-galvanised according to NF EN 10346 (S220 GD / Z).
SZ : Tôle d'acier galvanisé avant fabrication suivant NF EN 10346 (S220 GD / Z).



www.niedaxfrance.fr

| | | |
|--|--|---|
| CONCAVE GBRs H24 SZ GBRS INSIDE BEND H24 G | |  |
| ASSISTANCE TECHNIQUE +33 (0)1 55 95 92 17 pole.technique@niedax.fr | |  |
| FT02727 | | |