

PRODUCT-DETAILS

OTR45BA3M

OTR45BA3M Enclosed Switch Disconnecter



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | OTR45BA3M |
| Code de produit | 1SCA022569R6350 |
| EAN | 6417019183817 |
| Description courte | OTR45BA3M Enclosed Switch Disconnecter |
| Description longue | Encl. Switch Disconnecter, 3-p. 415V AC23 45A, 22kW. Stainless steel enclosure. IP65. RedYellow Selector handle. Interlocked cover. Defeatable interlocking. The enclosure of the OTR series is made of rigid stainless steel, class AISI304. The enclosure has a hinged door, with door lock. The cover is interlocked, and can not be opened when switch is on. The interlock function can be defeated for thermographing. Suitable for outdoor and indoor use. The cable entries are of knock out types. N- and PE terminal included. |

Valeur Circulaire

| | |
|---|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 1SCC340076D0201 |
| Informations RoHS | 1SCC340075D0201 |
| Toxic Substances Control Act - TSCA | 1SCC340095D0201 |

Commande

| | |
|------------------|---------|
| Quantité minimum | 1 pièce |
|------------------|---------|

| | |
|----------------|---------------|
| Code douanier | 85363030 |
| Pays d'origine | Bulgaria (BG) |

Downloads Préférés

| | |
|--|-------------------|
| Fiche produit, informations techniques | 1SCC340015C0201 |
| Instructions et manuels | 1SCC340006M0013 |
| Mechanical Drawings | OTLK201510S32.stp |

Dimensions

| | |
|----------------------|--------|
| Produit Largeur Net | 150 mm |
| Produit Hauteur Net | 200 mm |
| Produit Longueur Net | 100 mm |
| Poids net | 1.8 kg |

Technique

| | |
|---|---|
| Rated Operational Current AC-21A (I_e) | (380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A |
| Rated Operational Current AC-22A (I_e) | (380 ... 415 V) 63 A (690 V) 63 A |
| Rated Operational Current AC-23A (I_e) | (380 ... 415 V) 45 A (500 V) 45 A (690 V) 20 A |
| Rated Operational Power AC-23A (P_e) | (380 ... 415 V) 22 kW (500 V) 22 kW (690 V) 15 kW |
| Conventional Thermal Current (I_{the}) | Fully Enclosed 63 A |
| Tension assignée d'isolement (U_i) | acc. to IEC/EN 60664-1 750 V |
| Tension | Circuit principal 750 V |
| Rated Short-Circuit Making Capacity (I_{cm}) | (690 V AC) 1.4 kA |
| Courant assigné de courte durée admissible (I_{cw}) | for 1 s 1 kA |
| Power Loss | at Rated Operating Conditions per Pole 1.5 W |
| Degré de pollution | 3 |
| Handle Color | Red / Yellow |
| Handle Type | Selector handle |
| Position of Line Terminals | Top In - Bottom Out |
| Normes et standards | IEC 60947-1, -3 |
| Fonctions spéciales | EMC |
| Nombre de pôles | 3 |
| Neutral Type | Detachable neutral |
| Connecting Capacity Main Circuit | Screw Clamp 1.5 ... 35 mm ² Screw Clamp / PE Terminal 2pc, 1.5 ... 25 mm ² |
| Section de câble | 1.5 ... 35 mm ² |
| Cable Entry Position | Top and/or Bottom |
| Cable Outlets Per Side | 2xø32.5+ø16.5 / 2xø32.5+ø16.5 |
| Indice de protection | acc. to IEC 60529 IP65 |

| | |
|------------------------------------|---------------------|
| Résistance aux chocs | Housing IK09 |
| Matériau du boîtier | Stainless steel |
| Maximum Mounted Auxiliary Contacts | 1 NO, 2 NC |
| Mounted Auxiliary Contacts | 0 NO, 0 NC |
| Number of Auxiliary Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 0 |
| Position of Neutral Terminals | Top In - Bottom Out |
| Position of PE Terminals | Top In - Bottom Out |
| Couple de serrage | Main Circuit 2 N·m |

Technique UL/CSA

| | |
|-------------------|--------------------|
| Couple de serrage | Main Circuit 2 N·m |
|-------------------|--------------------|

Environnement

| | |
|-------------------------------------|-----------------------------------|
| Statut RoHS | Following EU Directive 2011/65/EU |
| Toxic Substances Control Act - TSCA | 1SCC340095D0201 |

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|-----------------|
| Déclaration de Conformité - CE | 1SCC340006D2704 |
| REACH Declaration | 1SCC340076D0201 |

Emballage

| | |
|-----------------------------|---------------|
| Emballage Niveau 1 Unités | box 1 pièce |
| Emballage Niveau 1 Largeur | 162 mm |
| Emballage Niveau 1 Longueur | 222 mm |
| Emballage Niveau 1 Hauteur | 148 mm |
| Emballage Niveau 1 Poids | 1.9 kg |
| Emballage Niveau 1 EAN | 6417019183817 |

Classifications

| | |
|--------------------------------|--|
| Code de classification d'objet | Q |
| ETIM 7 | EC000216 - Switch disconnecter |
| ETIM 8 | EC000216 - Switch disconnecter |
| ETIM 9 | EC000216 - Switch disconnecter (low voltage) |
| eClass | V11.1 : 27371403 |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |

Catégories

Produits basse tension → Interrupteurs et appareillage à fusibles en coffret → Interrupteurs-sectionneurs en coffret → Enclosed Switch-Disconnectors

