

Jupiter, Tellus, Polar, 230V



230V, 50Hz, max 50W, GU10, Class II, IP23*

0,5 - 1,0 mm² 8 mm

1,5 - 2,5 mm² 12 mm

ca 10° (max. 20°)

Max 16A

0,5m

Halogen

0,05m

7W LED

| | | h (min.) (mm) | (mm) |
|---------|---------------------|---------------------|----------|
| Jupiter | 230 V | 110 | 84 |
| Jupiter | LED 230 V | | |
| Jupiter | Exclusive 230 V | | |
| Jupiter | Exclusive LED 230 V | | |
| Jupiter | Soft 230 V | | |
| Jupiter | Soft LED 230 V | 135 | 84 |
| Jupiter | Outdoor 230 V | 130 | |
| Jupiter | Outdoor LED 230 V | 110 | 84 |
| Tellus | 230 V | | |
| Tellus | LED 230 V | 110 | 72 |
| Tellus | Exclusive 230 V | | |
| Tellus | Exclusive LED 230 V | 130 | |
| Polar | 230 V | 110 | 72 |

NO: Minimumsavstand til brennbart materiale i armaturens stråleretning.

EN: Minimum distance to flammable material in the beam direction.

FR: Distance minimum entre le faisceau lumineux de l'armature et toute matière inflammable.

NL: Minimale afstand tussen de lichtstraal van de armatuur en het brandbaar materiaal.

DE: Der kleinste Abstand zum brennbaren Material in die Richtung des Lichtstrahls.

SG Multibox

SG Downlightbox

SG Sealbox & Frame

Rev. 01.06.2011

SG Armaturen AS
Svaabekk Industriområde
N-4790 Lillesand
NORGE
Tel: +47 37 26 84 84
www.sg-as.no

SG Armaturen AB
August Barksg. 30B
SE-421 32 Västra Frölunda
SVERIGE
Tel: +46 31 81 71 10
www.sg-ab.se

SG Lighting SA/NV
Wayenborgstraat 4
B-2800 Mechelen Noord II
BELGIQUE/BELGIË
Tel: +32 (0) 15 20 72 71
www.sglighting.net

SG Lighting SA/NV
Parc de l'Arboretum
73 rue de Saint Mandrier
83140 Six Fours Les Plages
FRANCE
Tel: +33 04 94 93 00 00
www.sglighting.net

SG Leuchten GmbH
Nordstrasse 53
D-59399 Olfen
DEUTSCHLAND
Tel: 0152-57000500
www.sg-leuchten.de

Jupiter, Tellus, Polar, 12V



12V, max 35W, GU/GX5.3, Class III, IP44*

0,5 - 1,0 mm² 8 mm

1,5 - 2,5 mm² 12 mm

Max 16A

ca 10° (max. 20°)

Max 2:

| | h (min.) | |
|-----------------------|----------|-------|
| Jupiter 12V | 130mm | Ø84mm |
| Jupiter Exclusive 12V | 130mm | Ø84mm |
| Jupiter Outdoor 12V | 130mm | Ø84mm |
| Jupiter Soft 12V | 130mm | Ø84mm |
| Tellus 12V | 130mm | Ø84mm |
| Polar 12V | 130mm | Ø72mm |

*

0,5m

NO: Minimumsavstand til brennbart materiale i armaturens stråleretning.
 EN: Minimum distance to flammable material in the beam direction.
 FR: Distance minimum entre le faisceau lumineux de l'armature et toute matière inflammable.
 NL: Minimale afstand tussen de lichtstraal van de armatuur en het brandbaar materiaal.
 DE: Der kleinste Abstand zum brennbaren Material in die Richtung des Lichtstrahls.

NO: Skadet glass må erstattes med nytt.
 EN: Damaged glass must be replaced.
 FR: Tout verre endommagé doit être remplacé.
 NL: Gebroken glas moet vervangen worden.
 DE: Glasscherben müssen ausgetauscht werden.

Rev. 26.05.2011

SG Armaturen AS
 Svaabekk Industriområde
 N-4790 Lillesand
 NORGE
 Tel: +47 37 26 84 84
 www.sg-as.no

SG Armaturen AB
 August Barksg. 30B
 SE-421 32 Västra Frölunda
 SVERIGE
 Tel: +46 31 81 71 10
 www.sg-ab.se

SG Lighting SA/NV
 Wayenborgstraat 4
 B-2800 Mechelen Noord II
 BELGIQUE/BELGIË
 Tel: +32 (0) 15 20 72 71
 www.sglighting.net

SG Lighting SA/NV
 Parc de l'Arboretum
 73 rue de Saint Mandrier
 83140 Six Fours Les Plages
 FRANCE
 Tel: +33 04 94 93 00 00
 www.sglighting.net

SG Leuchten GmbH
 Nordstrasse 53
 D-59399 Olfen
 DEUTSCHLAND
 Tel: 0152-57000500
 www.sg-leuchten.de