Part number CX 04 SCF-H





Female modular insert, Mixo Data series, fibre optic, 4 poles, 1 module, with metallic sleeve


Product description		Material propertie
Product type	Modular insert	Main material
Series	Mixo Data	Colour
Connection type	Fibre optic	RoHs conformity
Gender	Female	China RoHs - EFUF
N. of poles	4 seats for fibre optic SC contacts	REACH SVHC subs
Size	1 module	Approvals / Stand
Specification	With metallic sleeve SC fibre optic connector	Certifications UL
Technical data		cUL
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure	General ordering
Further technical details		EAN13 code
Mating cycles	≥ 500	eCl@ss 8.1
Insulation resistance	≥ 10 GΩ	ETIM 7.0
Weight	10,00 g	Packaging Informa
Operating temperature		Sub-packaging de
range (min, max)	-40°C +85°C	Sub-packaging qu
UL 94 flammability rating	V-0	Sub-packaging EA barcode

Material properties		
Main material	Polycarbonate (PC)	
Colour	RAL 7032 grey	
RoHs conformity	Compliant	
China RoHs - EFUP	E	
REACH SVHC substances	No	
Approvals / Standards		
Certifications	DNV, BV	
UL	ECBT2	
cUL	ECBT8	
General ordering information		
EAN13 code	8015747190176	
eCl@ss 8.1	27440205	
ETIM 7.0	EC000438	
Packaging Information		
Sub-packaging description	Plastic bag	
Sub-packaging quantity	1 Pcs	
Sub-packaging EAN barcode	8015747225182	





Catalogue drawings



Notes

Standard modular inserts:

-in combination with standard contacts and standard frames (CX ... TF/TM); must be mounted either in traditional enclosures or in COB panel supports (both up to 500 matings).

Dimensions shown in mm are not binding and may be changed without notice.