




Coude à secteurs (&gt; Ø 200)



Coude embouti (≤ Ø 200)



Coude avec joints



Coude à 45° et 30°



## COUDES À 90°

DIMENSIONS (mm)	
Ø D	
80	
100	
125	
160	
200	
250	
315	
355	
400	
450	
500	
560	
630	
710	
800	
900	

GALVA STANDARD	
REF	CODE
C 80/90	523 219
C 100/90	523 850
C 125/90	523 521
C 160/90	523 522
C 200/90	523 523
C 250/90	523 524
C 315/90	523 525
C 355/90	523 528
C 400/90	523 526
C 450/90	523 238
C 500/90	523 527
C 560/90	543 101
C 630/90	523 142
C 710/90	523 942
C 800/90	523 328
C 900/90	533 113

GALVA AVEC JOINTS	
REF	CODE
C 80/90 J	547 373
C 100/90 J	529 600
C 125/90 J	529 601
C 160/90 J	529 602
C 200/90 J	529 603
C 250/90 J	529 604
C 315/90 J	529 605
C 355/90 J	529 606
C 400/90 J	529 607
C 450/90 J	529 608
C 500/90 J	529 609
C 560/90 J	529 069
C 630/90 J	547 303
-	-
-	-
-	-

ALUMINIUM STANDARD	
REF	CODE
-	-
C 100/90 AL	543 207
C 125/90 AL	523 884
C 160/90 AL	523 885
C 200/90 AL	523 886
C 250/90 AL	523 887
C 315/90 AL	523 888
C 355/90 AL	523 747
C 400/90 AL	523 748
C 450/90 AL	524 014
C 500/90 AL	523 749
C 560/90 AL	543 600
C 630/90 AL	533 665
-	-
-	-
-	-

## COUDES À 45°

DIMENSIONS (mm)	
Ø D	
80	
100	
125	
160	
200	
250	
315	
355	
400	
450	
500	
560	
630	
710	
800	

GALVA STANDARD	
REF	CODE
C 80/45	543 171
C 100/45	523 851
C 125/45	523 539
C 160/45	523 533
C 200/45	523 534
C 250/45	523 537
C 315/45	523 538
C 355/45	523 529
C 400/45	523 531
C 450/45	523 237
C 500/45	523 532
C 560/45	543 303
C 630/45	523 143
C 710/45	543 173
C 800/45	523 329

GALVA AVEC JOINTS	
REF	CODE
C 80/45 J	547 600
C 100/45 J	529 650
C 125/45 J	529 651
C 160/45 J	529 652
C 200/45 J	529 653
C 250/45 J	529 654
C 315/45 J	529 655
C 355/45 J	529 656
C 400/45 J	529 657
C 450/45 J	529 658
C 500/45 J	529 659
C 560/45 J	529 125
C 630/45 J	547 304
-	-
-	-

ALUMINIUM STANDARD	
REF	CODE
-	-
C 100/45 AL	543 165
C 125/45 AL	523 892
C 160/45 AL	523 893
C 200/45 AL	523 894
C 250/45 AL	523 895
C 315/45 AL	523 896
C 355/45 AL	523 750
C 400/45 AL	523 751
C 450/45 AL	524 015
C 500/45 AL	523 752
-	-
-	-
-	-

## COUDES À 30°

DIMENSIONS (mm)	
Ø D	
125	
160	
200	
250	
315	
355	
400	
450	
500	
630	

GALVA STANDARD	
REF	CODE
C 125/30	523 692
C 160/30	523 693
C 200/30	523 694
C 250/30	523 695
C 315/30	523 696
C 355/30	523 697
C 400/30	523 698
C 450/30	523 707
C 500/30	523 699
C 630/30	523 619

GALVA AVEC JOINTS	
REF	CODE
C 125/30 J	529 122
C 160/30 J	529 121
C 200/30 J	529 120
C 250/30 J	529 119
C 315/30 J	529 100
C 355/30 J	529 118
C 400/30 J	529 117
C 450/30 J	529 116
C 500/30 J	529 113
C 630/30 J	529 114