

KIT GALAXY LED 10




Corps aluminium. Orientable. Kit prêt-à-poser. **LED SHARP.**

	QPAR 16		GU10	10W
	230V	IP20 IK02	850°	35 000 h

Lumens	Teinte	Couleur	Code avec lampe
700	2700 K	blanc	51036
750	4000 K	blanc	51037
700	2700 K	nickel	51038
750	4000 K	nickel	51039

Dimmable avec variateur universel.



LED 10	2700 K	10 W	38°
	h (m)	E _{max} (lx)	d (m)
	1	1650	0,69
	2	413	1,4
	2,5	264	1,7

LED 10	4000 K	10 W	38°
	h (m)	E _{max} (lx)	d (m)
	1	1890	0,69
	2	473	1,4
	3	210	2,1

KIT GALAXY LED 8 / LED 6





Corps aluminium. Orientable. Kit prêt-à-poser. **LED SHARP.**

	230V	IP20 IK02	850°	35 000 h
--	------	-----------	------	----------

	QPAR 16		GU10	8W
--	---------	--	------	----

Lumens	Teinte	Couleur	Code avec lampe
650	2700 K	blanc	51040
700	4000 K	blanc	51041
650	2700 K	nickel	51042
700	4000 K	nickel	51043



LED 8	2700 K	8 W	55°
	h (m)	E _{max} (lx)	d (m)
	1	837	1,04
	2	209	2,1
	3	93	3,1

LED 6	2700 K	6 W	45°
	h (m)	E _{max} (lx)	d (m)
	1	576	0,83
	2	144	1,7
	2,5	92	2,1

LED 8	4000 K	8 W	55°
	h (m)	E _{max} (lx)	d (m)
	1	861	1,04
	2	215	2,1
	3	96	3,1

LED 6	4000 K	6 W	45°
	h (m)	E _{max} (lx)	d (m)
	1	667	0,83
	2	167	1,7
	2,5	107	2,1

	QPAR 16		GU10	6W
--	---------	--	------	----

Lumens	Teinte	Couleur	Code avec lampe
400	2700 K	blanc	5205
450	4000 K	blanc	5204
400	2700 K	nickel	5238
450	4000 K	nickel	5239