

---

## LINEAR LED 1200 14 W 4000 K

LEDVANCE LINEAR LED | LED batten luminaires



---

### Areas of application

- General indoor illumination
- Corridors
- Entrance lighting
- Accent lighting
- Public areas
- Cove lighting
- Shelves, furniture integration or under cabinet mounting
- Seamless linear lighting

---

### Product benefits

- Compact dimensions
- Easy to install in two different mounting angles
- Energy savings of up to 45 % compared to conventional linear luminaires
- Rows of up to 10 luminaires possible
- For seamless lines of light without dark spots

---

### Product features

- High luminous efficacy: up to 100 lm/W
- Luminous flux: up to 1,450 lm
- Available with color temperature: 3,000 K, 4,000 K
- Beam angle: 140°
- Type of protection: IP20
- Lifetime: up to 30,000 h
- On/off switch on luminaire
- Different lengths available
- Certificates: CE, CB, TUEV SUED



# Product datasheet

---

## Technical data

### Electrical data

Operating mode	ECG
Nominal wattage	14.00 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Nominal current	0.061 A

### Photometrical data

Color temperature	4000 K
Luminous flux	1500 lm
Light color (designation)	Cool White
Color rendering index Ra	>80

### Light technical data

Beam angle	140 °
------------	-------

### Dimensions & weight

---



Length	1173 mm
Width	28.0 mm
Height	36.0 mm
Product weight	410.00 g

### Colors & materials

Body material	Aluminum
Product color	White

### Temperatures & operating conditions

---

## Product datasheet

Ambient temperature range	-20...40 °C
---------------------------	-------------

### Lifespan

Lifespan	30000 h
----------	---------

### Capabilities

Dimmable	No
Type of connection	Plug, EU

### Certificates & standards

Protection class	II
Type of protection	IP20
Protection class IK (shock resistance)	IK02

### Equipment / Accessories

– Complete mounting and connecting accessories included

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075000346	LINEAR LED 1200 14 W 4000 K	Shipping carton box 25	1418 mm x 233 mm x 180 mm	59.47 dm <sup>3</sup>	13942.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.