

## Features

Use: Indoor  
Type of installation: SUSPENDED, CEILING MOUNTED  
Emission: DIRECT  
Optics: OPAL  
Colour: BLACK  
Dimming: PUSH, DALI  
Emergency: NO  
L: 2400mm  
A: 38mm  
H: 65mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 4.1kg

## Tech data

Luminaire input power: 39.1W  
Luminaire luminous flux: 3438lm  
IP: 40  
Insulation class: I  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 35W  
Source luminous flux: 5967lm  
Colour temperature: 4000K  
CRI: >80  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)



## SCREENS



LUCKY MINI: DIFF. OPALE L=6500

103507.99



LUCKY MINI: DIFF. OPALE PER L2400

103506.99


## COMPLETION ACCESSORIES



4x

KIT GIUNZIONE MODULI P-30/LUCKY MINI


103317.99



LUCKY MINI: COPPIA TESTATE NE

103509.02

## MOUNTING ACCESSORIES



KIT ALIMENTAZIONE L3000 5P NE

108922.02




LUCKY MINI: CAVO DI SOSPENSIONE L=3000

103513.99




ALL-TRACK: COPPIA ADATT. 3P+DALI NER

**106723.02**



KIT ALIMENTAZIONE L1200 3P NE

**108919.02**



KIT ALIMENTAZIONE L1200 5P NE

**108921.02**