



**CABLES MULTICONDUCTEURS  
SOUPLES – NON BLINDES**

**300/500 V**

**MULTICORE CABLES  
FLEXIBLE - UNSHIELDED**

Température maxi au conducteur : 70°C

Maximum conductor temperature : 70°C

LiYY	Diamètre extérieur <i>Outer diameter</i> (mm)	Poids de cuivre <i>Copper index</i> (Kg/km)	Masse <i>Weight Approx</i> (Kg/km)
2 x 0.14	3.3	2.7	14
3 x 0.14	3.5	4.1	17
4 x 0.14	3.7	5.4	20
5 x 0.14	4.0	6.7	22
6 x 0.14	4.4	8.1	27
7 x 0.14	4.4	9.5	30
8 x 0.14	4.7	10.7	35
10 x 0.14	5.4	13.5	43
12 x 0.14	5.6	16.1	49
16 x 0.14	6.2	21.6	60
21 x 0.14	7.4	28.4	77
24 x 0.14	8.0	32.4	90
27 x 0.14	8.4	36.5	97
30 x 0.14	8.6	40.5	110
36 x 0.14	9.2	48.6	130
44 x 0.14	10.3	59.4	160
48 x 0.14	10.4	65.0	164
52 x 0.14	10.9	70.2	175
61 x 0.14	11.5	82.4	208
80 x 0.14	15.9	108	285
100 x 0.14	18.1	135	370
2 x 0.25	4.0	4.8	17
3 x 0.25	4.2	7.2	21
4 x 0.25	4.5	9.6	26
5 x 0.25	4.8	12.0	33
6 x 0.25	5.0	14.4	41
7 x 0.25	5.2	16.8	43
8 x 0.25	6.0	19.2	49
10 x 0.25	6.8	24.0	59
12 x 0.25	7.2	28.8	68
16 x 0.25	7.9	38.4	85
21 x 0.25	9.0	50.0	106
24 x 0.25	9.8	58.0	122
27 x 0.25	10.0	65.0	142
30 x 0.25	10.6	72.0	157
44 x 0.25	12.8	106	220
52 x 0.25	13.6	125	265

LiYY	Diamètre extérieur <i>Outer diameter</i> (mm)	Poids de cuivre <i>Copper index</i> (Kg/km)	Masse <i>Weight Approx</i> (Kg/km)
61 x 0.25	14.4	146	308
80 x 0.25	19.6	192	450
100 x 0.25	23.1	240	590
2 x 0.34	4.2	6.5	23
3 x 0.34	4.4	9.8	30
4 x 0.34	4.9	13.1	44
5 x 0.34	5.3	16.3	54
6 x 0.34	5.8	19.6	58
7 x 0.34	5.9	22.8	62
8 x 0.34	6.4	26.1	73
10 x 0.34	7.5	32.6	82
12 x 0.34	7.6	39.2	102
16 x 0.34	8.4	52.0	126
21 x 0.34	9.8	69.0	167
24 x 0.34	11.0	78.0	188
27 x 0.34	11.2	88.0	206
30 x 0.34	11.8	98.0	226
36 x 0.34	12.7	118	286
44 x 0.34	14.7	144	370
52 x 0.34	15.3	170	430
61 x 0.34	16.2	199	508
80 x 0.34	22.0	264	880
100 x 0.34	25.4	327	1050
2 x 0.50	4.8	9.6	40
3 x 0.50	5.1	14.4	46
4 x 0.50	5.8	19.2	55
5 x 0.50	6.3	24.0	64
7 x 0.50	7.1	33.6	81
8 x 0.50	7.8	38.4	97
10 x 0.50	8.8	48.0	116
12 x 0.50	9.1	58.0	135
16 x 0.50	10.5	77.0	168
20 x 0.50	11.7	96.0	213
24 x 0.50	12.7	116	266
30 x 0.50	13.7	144	303
40 x 0.50	15.6	192	391

