

PRODUCT-DETAILS

# CE3T-10R-01

## CE3T-10R-01 Emergency stop



### Informations générales

Extension du type de produit	CE3T-10R-01
Code de produit	1SFA619500R1041
EAN	7320500260692
Description courte	CE3T-10R-01 Emergency stop
Description longue	<p>The CE3T-10R-01 Emergency stop is: Compact - Emergency stop - Twist release - Maintained - Mushroom 30mm - Red - Non-illuminated - 1NC - 0 NO - 1 NC - 24 ... 300 V</p> <p>This Emergency stop is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost.</p> <p>The compact range has a high level of dust and water resistance.</p>

### Commande

Quantité minimum	10 pièce
Code douanier	8536500000

### Downloads Préférés

Fiche produit, informations techniques	1SFC151007C02_
Instructions et manuels	1SFC151011M0201

## Dimensions

Produit Largeur Net	0.03 m
Produit Hauteur Net	0.03 m
Produit Longueur Net	0.073 m
Poids net	0.034 kg

## Technique

Température de l'air ambiant	Operation -25 ... +70 °C Storage -40 ... +85 °C
Couleur	Red
Actuator Type	Mushroom 30mm
Bezel Material	n/a
Voyant	Non-illuminated
Fonction	Maintained
Sub-Function	Twist release
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	0
Indice de protection	Front IP66 Front IP67 Front IP69K Terminals IP20
Classe de protection (NEMA)	Type1 Type12 Type13 Type3R Type4 Type4X
Degré de pollution	3
Tension assignée d'isolement ( $U_i$ )	300 V
Tension assignée de tenue aux chocs ( $U_{imp}$ )	6 kV
Fréquence assignée (f)	50 / 60 Hz
Tension	24 ... 300 V
Courant assignée d'emploi DC-13 ( $I_e$ )	(24 V) 0.3 A (125 V) 0.2 A
Courant assignée d'emploi AC-15 ( $I_e$ )	(240 V) 1 A
Power Loss	Maximum 2.5 W
Durabilité mecanique	0.5 million
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm <sup>2</sup> Flexible with Ferrule 2 x 0.5...1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1 x 0.5...1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2 x 0.5...1.5 mm <sup>2</sup> Flexible 1 x 0.5 ...1.5 mm <sup>2</sup> Flexible 2 x 0.5 ...1.5 mm <sup>2</sup> Solid 1 x 0.5...1.5 mm <sup>2</sup> Solid 2 x 0.5...1.5 mm <sup>2</sup>

Type de raccordement	Screw Clamp
Type de borne	Screw Terminals
Couple de serrage	0.8 N·m
Wire Stripping Length	6 mm

## Technique UL/CSA

Connecting Capacity	1x 22...14 AWG
UL/CSA	2x 22...14 AWG

## Environnement

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
---	-----------------

Informations RoHS	2CMT2019-005802
-------------------	-----------------

Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

SCIP	c859009c-dc65-4e4d-8006-77b85b56fa30 Sweden (SE)
------	--

SCIP simplifié	744766bc-cdd3-4926-975c-e221f3578bbf Estonia (EE) b129f2bd-d958-4c5a-a342-f35c68513bbb Greece (GR) a4e74ad9-a4a9-4318-a2e1-69297224eb96 Hungary (HU) 492f12c0-5763-4bd5-a39e-12c5d5d45d25 Belgium (BE) 1189b362-5866-41e2-a30a-cafd111033a7 Spain (ES) 47d619ea-d2df-4c4f-aab6-b31eda401a57 Germany (DE) ef9cbfef-f7d2-41ea-a453-e81373a16955 Germany (DE) c23bea4d-dbb5-40ca-b975-8028ba56608f Hungary (HU) 598a84a9-5cb4-4951-8c5c-4f2b93d9b97c France (FR) c1414e50-e90d-40b6-8446-efd65c880f5f Poland (PL) ea18b805-ef4e-4110-bf81-a17ab5b08685 Germany (DE) 57072c90-1ef1-4be7-8b26-f321b1167712 Belgium (BE) 3c8f095e-6efb-4182-a469-7882a2ad29c6 Denmark (DK) bc106146-654e-4a7b-9eb0-787794a85b28 Germany (DE) b579237c-502c-4e75-9599-1d7ba7df0c88 Italy (IT) a7dbbc93-fdf9-4f35-9f2b-5e6e3e380e0b Poland (PL) 4421749b-84cd-4a86-98cf-b30f9ecb17ff Croatia (HR) 7db1ba7d-2ff7-4f9f-81e7-34b9efa714e0 Netherlands (NL) c5685138-30dd-4277-b3e8-b1768f8e2fe9 Czech Republic (CZ) 13cbfdf3-0049-4ac4-90f6-b1e0699a78cf France (FR) 12b5619e-c930-487b-b347-b304af2a8f3e Poland (PL) d5b9d777-daf5-48ab-a5d5-6d47f81378e4 Sweden (SE) e20a0ffd-65c7-492a-a524-399da46fdd3a Bulgaria (BG) 7ddd3f50-4a06-4e4f-9a19-02d04c6a608b Portugal (PT) b7a527de-58bc-4335-96f0-12899f2dd9d9 Finland (FI) d2cfd4ae-677a-48c9-8562-0bd958a19ddd Norway (NO)
----------------	---

WEEE B2C / B2B	Business To Business
----------------	----------------------

Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
----------------	--

## Certificats et Déclarations (Numéro de document)

CB Certificate	CN54150 CQC_CN_CN50749
----------------	---------------------------

CQC Certificate	CQC2003010305054693
-----------------	---------------------

Certificat ecULus	UL_E496500-20171020
-------------------	---------------------

Declaration of Conformity - CCC	2020980305001187
---------------------------------	------------------

Déclaration de Conformité	2CMT2019-005802
---------------------------	-----------------

- CE

Declaration of Conformity 2CMT2020-006122

- UKCA

DNV GL Certificate 9AKK107046A3749

EAC Certificate EAC RU C-CN.ME77.B.00537/19

---

## Emballage

Emballage Niveau 1 Unités	bag 1 pièce
Emballage Niveau 1 Largeur	0.165 m
Emballage Niveau 1 Longueur	0.09 m
Emballage Niveau 1 Hauteur	0.035 m
Emballage Niveau 1 Poids	0.036 kg
Emballage Niveau 1 EAN	7320500260692

---

## Classifications

Code de classification d'objet	S
ETIM 6	EC002034 - bouton-poussoir ARRET D'URGENCE, appareil complet
ETIM 7	EC002034 - Emergency stop complete
ETIM 8	EC002034 - Emergency stop complete
eClass	V11.0 : 27371244
UNSPSC	39122216
Code de catégorie granulaire IDEA (IGCC)	5212 >> Push button for distribution board
E-Number (Finland)	2313520
E-Number (Norway)	4372730
E-Number (Sweden)	3711500

---

## Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Unités de commande et de signalisation → Compact Range → CE Compact Emergency Stops and Machine Stops

