

SmartZone™ G5 Serial Communication Cable

specifications

The G5 Serial Communication cable (RJ45-DB9) is used to establish a serial connection between a computer and iPDU. This cable enables data center administrators to perform basic management tasks over the Command Line Interface (CLI).



**SmartZone™ G5
Serial Communication Cable**

**Serial Communication
Cable:** MA001

technical information

Attached Cable Length: Supplied with 11.8 inches [30cm] cable terminating in RJ45 socket

*Mounting hardware not included

key features and benefits

RJ45 Connection Utilizes an RJ45 plug and DB9 connection to a computer and iPDU

applications

The SmartZone™ Serial Communication Cable (RJ45-DB9) is used to establish a serial connection between a computer and iPDU. Simply connect the RJ45 end of the serial communication cable into the Serial+RS485-1 port on the iPDU. Connect the DB9 end of the cable into the serial port (COM) on a computer. Note: A DB9 serial to USB connection cable may be required, depending on hardware configuration. Then, use the connected computer to open a communications program such as HyperTerminal or PuTTY. Select the appropriate COM port and confirm the port settings are as follows:

- Bits per second: 115200
- Data bits: 8
- Stop bits: 1
- Parity: None
- Flow control: None

The iPDU is connected and ready for communication.

SmartZone™ G5 Serial Communication Cable

technical specification

Electrical	
Operational voltage	5V DC
Physical	
Length	1m
Wire Type	CAT.5E Patch Cable, UTP
Environmental	
Maximum elevation, above MSL (Operating/Storage)	0-10000 feet (0-3048m)/0-50000 feet (0-15240 m)
Temperature (Operating/Storage)	0°C~+70°C (32~ 158°F)/-20~ + 70°C (-4 ~ 158°F)
Humidity (Operating/Storage)	0-95% RH, non-condensing
Compliance	
Environmental Verification	ROHS, WEEE

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT US/CANADA
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
cs-emea@panduit.com
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
cs-ap@panduit.com
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
cs-japan@panduit.com
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA
Guadalajara, Mexico
cs-la@panduit.com
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
cs-aus@panduit.com
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information

Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com
or by phone: 800.777.3300

PANDUIT®

©2017 Panduit Corp.
ALL RIGHTS RESERVED.
PUSP67--WW-ENG
9/2017