

wall mounting socket outlet - with pilot contact



Product description	
BALS-Prd.-Nr	1127-P
EAN	4024941966115
Product category	Wall mounting socket outlet
Current	63A
Number of poles	4p
Number of poles	3P+PE
Position of earth contact	6 h
Voltage	380 up to 415V
Frequency	50 and 60Hz

Product description	
Protection degree	IP44
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Housing bottom grey RAL 7035, Housing top grey RAL 7035
Connection design	kontex contact
Maximum conductor size	25.0 qmm
Cable entry	top entry M40, bottom entry M32
Height	226mm
Width	118mm
Depth	173mm
dimension of enclosure (GG)	170x118 mm (HxW)
Material of enclosure	Polycarbonate
Contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	The cable entry is one at top open and two at bottom closed, with pilot contact
	Lower part of housing rotatable by 180°

Logistics data	
Weight/pcs	0.835 kg / Piece
Packaging	Bag

Logistics data	
Content amount	1 ST
EAN	4024941966115
Length	168 mm
Width	118 mm
Height	223 mm
Weight	0.836 kg
Volume	4,420.752 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941965576
Length	345 mm
Width	345 mm
Height	217 mm
Weight	4.51 kg
Volume	24,276 ccm



Ampere Polzahl	63 3	63 4	63 5			
a	118,0	118,0	118,0			
b	170,0	170,0	170,0			
c	223,0	223,0	223,0			
d	168,0	168,0	168,0			
e	104,0	104,0	104,0			
f	136,0	136,0	136,0			
h ø	6,1	6,1	6,1			
i	6,0	6,0	6,0			
k	M40	M40	M40			
l	M 32/32	M 32/32	M 32/32			
Leiter mm ² min	6	6	6			
Leiter mm ² max	25	25	25			