

Part number

MFON 16.32



Hood, LS-TYPE series, with 4 pegs, M32 side cable entry without adapter, size "77.27", high construction

Product description		Material properties	
Product type	Hood	Colour	RAL 9005 black
Series	LS-TYPE	RoHs conformity	Compliant
Closing type	With 4 pegs	China RoHs - EFUP	E
Size	Size 77.27	REACH SVHC substances	No
Cable entry	Side cable entry M32	Approvals / Standards	
Specification	High construction	Certifications	DNV, BV
Technical data		UL	ECBT2
IP degree of protection	IP65	cUL	ECBT8
Further technical details		General ordering information	
Weight	258,00 g	EAN13 code	8015747044295
Operating temperature range (min, max)	-40°C...+125°C	eCl@ss 8.1	27440202
		ETIM 7.0	EC000437
		Packaging Information	
		Packaging length	190,00 mm
		Packaging height	140,00 mm
		Packaging width	290,00 mm
		Packaging weight	5,26 kg
		Packaging volume	7,71 dm ³
		Packaging description	Carton box
		Packaging quantity	20 Pcs
		Packaging EAN code	8015747187732
		Sub-packaging weight	1,32 kg
		Sub-packaging description	Plastic packaging
		Sub-packaging quantity	5 Pcs
		Sub-packaging EAN barcode	8015747187749

Part number MFON 16.32



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "77.27" **LS-TYPE version**

inserts:	page	housings with double lever	hoods with 4 pegs
CD	40 poles + @ 49+52 *		
CT, CTS **)	40 poles + @ 56 *		
CDD	72 poles + @ 62+65 *		
CDE	32 poles + @ 82+84 *		
CSH	16 poles + @ 90+92 *		
CCE	16 poles + @ 98+102 *		
CNE, CSE, JCNE, JCSE	16 poles + @ 99 and 108 *		
CSS	16 poles + @ 120+122 *		
CTE, CTSE **)	16 poles + @ 128 *		
CMSE	6+2 (aux) poles + @ 137 *		
CMCE	6+2 (aux) poles + @ 136 *		
CP	6 poles + @ 149+150 *		
CX	6/36 e 12/2 poles + @ 152+153 *		
CX	4/0 e 4/2 poles + @ 154 *		
MIXO	4 modules 160-195 *		

insert centre distance: 77,5 x 27 mm
* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with 2 levers	CHIN 16	M		
surface mounting housing, high construction, with 2 levers	MAPN 16.32	32		
with pegs, side entry			MHON 16.32	32
with pegs, side entry, high construction			MFON 16.32	32
with pegs, top entry			MHVN 16.32	32
with pegs, top entry, high construction			MFVN 16.32	32

**) only in the CHIN 16 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm	dimensions in mm
CHIN 16	MFON 16.32
MAPN 16.32	MFVN 16.32
	MHON 16.32
	MHVN 16.32

8

Notes

Dimensions shown in mm are not binding and may be changed without notice.