

Product type designation				GX20	
General characteristics					
Switching diagram				10	
N° of elements				2	
Contact characteristics					
Rated insulation voltage U_i	IEC/EN	V	690		
	UL/CSA	V	600		
Rated impulse withstand voltage U_{imp}			kV	6	
Conventional free air thermal current I_{th}	UL/CSA	A	15		
			V	440	
Rated operational voltage			V	440	
	Maximum fuse size for short-circuit protection I_n (gG)	25kA	A	16	
Rated short time current I_{cw}		1s	A	250	
	Operational current I_e IEC/EN	AC1/AC21A			A
AC15			110V	A	10
		220/230V	A	8	
		660/690V	A	3.7	
Rated operational power in AC	Single-phase AC-3	380/440V	kW	3	
		Three-phase AC23A	380/440V	kW	7.5
	Single-phase AC23A		380/440V	kW	3.5
			Rated operational current in DC	DC21A	48V
60V	A	20			
110V	A	4			
440V	A	0.25			
DC23A (poles in series)	24V	A		20 (1)	
	48V	A		20 (2)	
	60V	A		20 (3)	
	110V	A	10 (3)		
DC13	220V	A	8 (4)		
	24V	A	20		
	48V	A	16		
	60V	A	12		
	110V	A	1		
Conductor size	220V	A	0.4		
	440V	A	0.15		
	Mechanical features				
Terminals screw				M3	
Tightening torque for terminals max				Nm 0.8	
Conductor size					

AWG - Rigid cable

min	AWG	20
Max	AWG	14

AWG - Flexible cable

min	AWG	20
-----	-----	----

Conductor size (IEC) - Flexible cable

min	mm ²	0.5
Max	mm ²	2.5

Conductor size (IEC) - Rigid cable

Max	mm ²	2.5
-----	-----------------	-----

Mechanical life

cycles	5x10 ⁶
--------	-------------------

UL technical data

Motor power for direct-on-line control

for three-phase motor

240V	HP	3
480V	HP	5
600V	HP	5

for single-phase motor

120V	HP	0.75
240V	HP	1.5

Ambient conditions

Temperature

Operating temperature

min	°C	-25
max	°C	+55

Storage temperature

min	°C	-40
max	°C	+70

Resistance & Protection

Frontal IP degree

IP65

Terminals IP degree

IP20

ETIM classification

ETIM 8.0

EC001029 -
Selector switch,
complete