

PRODUCT-DETAILS

CL2-501G

CL2-501G Pilot Light



Informations générales

| | |
|------------------------------|---|
| Extension du type de produit | CL2-501G |
| Code de produit | 1SFA619403R5012 |
| EAN | 7320500556047 |
| Description courte | CL2-501G Pilot Light |
| Description longue | The CL2-501G Pilot Light is: Compact - Pilot Light - Pilot light head - Green - Illuminated - 12V DC This Pilot Light is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost. The compact range has a high level of dust and water resistance. |

Commande

| | |
|------------------|------------|
| Quantité minimum | 10 pièce |
| Code douanier | 8536619090 |

Downloads Préférés

| | |
|--|-----------------|
| Fiche produit, informations techniques | 1SFC151007C02_ |
| Instructions et manuels | 1SFC151011M0201 |

Dimensions

| | |
|----------------------|----------|
| Produit Largeur Net | 0.03 m |
| Produit Hauteur Net | 0.03 m |
| Produit Longueur Net | 0.052 m |
| Poids net | 0.018 kg |

Technique

| | |
|------------------------------|--|
| Température de l'air ambiant | Operation -25 ... +70 °C Storage -40 ... +85 °C |
| Couleur | Green |
| Actuator Type | Pilot light head |
| Voyant | Illuminated |
| Type de lampe | 12V DC, integrated LED |
| Indice de protection | Front IP66 Front IP67 Front IP69K Terminals IP20 |
| Classe de protection (NEMA) | Type1 Type12 Type13 Type3R Type4 Type4X |
| Degré de pollution | 3 |
| Tension | Supply Circuit 12V DC V |
| Connecting Capacity | Flexible with Ferrule 1 x 0.75...2.5 mm ² Flexible with Ferrule 2 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 1 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 2 x 0.75...2.5 mm ² Flexible 1 x 0.75 ... 2.5 mm ² Flexible 2 x 0.75 ... 2.5 mm ² Solid 1 x 0.75...2.5 mm ² Solid 2 x 0.75...2.5 mm ² |
| Type de raccordement | Screw Clamp |
| Type de borne | Screw Terminals |
| Couple de serrage | 0.9 N·m |
| Wire Stripping Length | 8 mm |

Technique UL/CSA

| | |
|---------------------|----------------|
| Connecting Capacity | 1x 18...14 AWG |
| UL/CSA | 2x 18...14 AWG |

Environnement

| | |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| Informations RoHS | 2CMT2015-005451 |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| WEEE B2C / B2B | Business To Business |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |

Certificats et Déclarations (Numéro de document)

| | |
|----------------|----------------|
| CB Certificate | CQC_CN_CN50749 |
|----------------|----------------|

| | |
|-------------------------------------|-----------------------------|
| Certificat ecULus | UL_E496500-20171020 |
| cURus Certificate | UL_E496500-20171020 |
| Déclaration de Conformité - CE | 2CMT2015-005451 |
| Declaration of Conformity - UKCA | 2CMT2020-006121 |
| DNV GL Certificate | 9AKK107046A3749 |
| EAC Certificate | EAC-RU C-CN.ME77.B.00690_20 |

Emballage

| | |
|--------------------------------|---------------|
| Emballage Niveau 1 Unités | bag 10 pièce |
| Emballage Niveau 1 Largeur | 0.235 m |
| Emballage Niveau 1 Longueur | 0.125 m |
| Emballage Niveau 1 Hauteur | 0.035 m |
| Emballage Niveau 1 Poids | 0.184 kg |
| Emballage Niveau 1 EAN | 7320500475799 |

Classifications

| | |
|---|--|
| Code de classification d'objet | P |
| ETIM 6 | EC000272 - voyant lumineux, appareil complet |
| ETIM 7 | EC000272 - Indicator light complete |
| ETIM 8 | EC000272 - Indicator light complete |
| eClass | V11.0 : 27371223 |
| UNSPSC | 39121534 |
| Code de catégorie granulaire IDEA (IGCC) | 4766 >> Indicator or pilot lights |
| E-Number (Finland) | 2313500 |
| E-Number (Norway) | 4373501 |
| E-Number (Sweden) | 3705746 |

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Unités de commande et de signalisation → Compact Range → CL Compact Pilot Lights

