

PRODUCT-DETAILS

# MC1CC00ATWG

## MC1CC00ATWG Mini Contactor 48 V DC - 3 NO - 1 NC - Screw Terminals



### Informations générales

|                              |  |
|------------------------------|--|
| Extension du type de produit | MC1CC00ATWG  |
| Code de produit              | 1SAL200796R9901  |
| EAN                          | 4013614543128  |
| Description courte           | MC1CC00ATWG Mini Contactor 48 V DC - 3 NO - 1 NC - Screw Terminals   |
| Description longue           | The MC1CC00ATWG mini contactor is a dimension optimized 4 pole contactor with screw terminals. This device is a great solution when high performances are needed but the space is limited. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 4 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. The product is equipped with an extended operating limits coil and it's suitable for wall or rail mounting. |

### Commande

|                  |          |
|------------------|----------|
| Quantité minimum | 1 pièce  |
| Code douanier    | 85365080 |

### Downloads Préférés

|                         |                 |
|-------------------------|-----------------|
| Instructions et manuels | 2CDC103061M6801 |
| CAD Dimensional Drawing | 2CDC001079B0201 |

---

## Dimensions

---

|                      |         |
|----------------------|---------|
| Produit Largeur Net  | 45 mm   |
| Produit Hauteur Net  | 48 mm   |
| Produit Longueur Net | 68 mm   |
| Poids net            | 0.25 kg |

---

## Technique

---

|  |  |
|--|--|
| Nombre de pôles  | 4  |
| Mini Contactor Type  | Mini Contactor   |
| Tension  | Circuit principal 690 V AC<br>Circuit principal 440 V DC   |
| Fréquence assignée (f)                                     | Circuit de commande DC<br>Circuit principal 50 Hz<br>Circuit principal 60 Hz<br>Circuit principal DC   |
| Tension assignée de tenue aux chocs ( $U_{imp}$ )          | Circuit principal 6 kV   |
| Tension assignée d'isolement ( $U_i$ )                     | 750 V  |
| Number of Main Contacts NC                                 | 1  |
| Number of Main Contacts NO                                 | 3  |
| Courant assignée d'emploi AC-1 ( $I_e$ )                   | (690 V) 55 °C 20 A<br>(690 V) 70 °C 16 A<br>(230 V) 55 °C 20 A<br>(230 V) 70 °C 16 A<br>(400 V) 55 °C 20 A<br>(400 V) 70 °C 16 A<br>(500 V) 55 °C 20 A<br>(500 V) 70 °C 16 A |
| Puissance assignée d'emploi AC-3 ( $P_e$ )                 | (230 V) Three Phase 2.2 kW<br>(400 V) Three Phase 4 kW<br>(500 V) Three Phase 4 kW<br>(690 V) Three Phase, NC 3 kW<br>(690 V) Three Phase, NO 4 kW                           |
| Courant assigné de courte durée admissible ( $I_{cw}$ )    | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 72 A  |
| Number of Auxiliary Contacts NC                            | 0  |
| Number of Auxiliary Contacts NO                            | 0  |
| Courant thermique conventionnel à l'air libre ( $I_{th}$ ) | Main Circuit 20 A  |
| Rated Control Circuit Voltage ( $U_c$ )                    | 48 V DC  |
| Plage d'utilisation de la bobine selon                     | (acc. to IEC 60947-4-1) for DC supply 0.85 ... 1.1 x $U_c$ (at $\theta \leq 55$ °C)  |
| Indice de protection                                       | Control Circuit Terminals IP20<br>Main Circuit Terminals IP20  |

|  |  |
|--|--|
| Durabilite mecanique                   | 10000000 cycle   |
| Maximum Electrical Switching Frequency | (AC-1) 300 cycles per hour<br>(AC-15) 360 cycles per hour<br>(AC-3) 1200 cycles per hour<br>(DC-1) 600 cycles per hour<br>(DC-13) 360 cycles per hour<br>(DC-3) 600 cycles per hour  |
| Connecting Capacity Main Circuit       | Flexible with Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Rigid 1x 0.75 ... 4 mm <sup>2</sup><br>Rigid 2x 0.75 ... 2.5 mm <sup>2</sup> |
| Connecting Capacity Control Circuit    | Flexible with Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Rigid 1/2x 0.75 ... 2.5 mm <sup>2</sup>                                      |
| Wire Stripping Length                  | Control Circuit 9 mm<br>Main Circuit 9 mm  |
| Couple de serrage                      | Control Circuit 0.8 N·m<br>Main Circuit 0.8 ... 1.0 N·m  |
| Recommended Screw Driver               | Pozidriv 2   |
| Montage sur rail DIN                   | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715   |
| Power Loss                             | at Rated Operating Conditions AC-1 per Pole 0.7 W  |
| Normes et standards                    | IEC/EN 60947-1<br>IEC/EN 60947-4-1<br>UL 60947-1<br>UL 60947-4-1   |

## Technique UL/CSA

|   |  |
|---|--|
| Maximum Operating Voltage UL/CSA        | Circuit principal 600 V AC   |
| Full Load Amps Motor Use                | (115 V AC) Single Phase 9.8 A<br>(200 V AC) Three Phase 11 A<br>(220 ... 240 V AC) Three Phase 9.6 A<br>(230 V AC) Single Phase 10 A<br>(440 ... 480 V AC) Three Phase 7.6 A<br>(550 ... 600 V AC) Three Phase 6.1 A |
| Puissance nominale UL/CSA               | (115 V AC) Single Phase 0.5 Hp<br>(200 V AC) Three Phase 3 Hp<br>(220 ... 240 V AC) Three Phase 3 Hp<br>(230 V AC) Single Phase 1.5 Hp<br>(440 ... 480 V AC) Three Phase 5 Hp<br>(550 ... 600 V AC) Three Phase 5 Hp |
| General Use Rating UL/CSA               | (600 V AC) 20 A  |
| Connecting Capacity Main Circuit UL/CSA | Stranded 1/2x 18-12 AWG  |
| Tightening Torque UL/CSA                | Control Circuit 7 in·lb<br>Main Circuit 7 in·lb  |

## Environnement

|   |  |
|---|--|
| Température de l'air<br>ambiant                     | Operation -40 ... +70 °C<br>Storage -55 ... +80 °C                     |
| Altitude de<br>fonctionnement maximale<br>autorisée | 3000 m   |
| Résistance aux chocs<br>selon CEI 60068-2-27        | 11 ms Pulse 25g  |
| Resistance to Vibrations<br>acc. to IEC 60068-2-6   | 5g / 3 ... 150 Hz  |
| Statut RoHS   | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

## Certificats et Déclarations (Numéro de document)

|                                     |                     |
|-------------------------------------|---------------------|
| Certificat BV                       | 1SAA971000-0201     |
| CB Certificate                      | 1SAA971000-2001     |
| CQC Certificate                     | CQC2019010304197131 |
| Declaration of Conformity<br>- CCC  | 2020980304001602    |
| Déclaration de Conformité<br>- CE   | 1SAD101100-3201     |
| Declaration of Conformity<br>- UKCA | 1SAD201100-3201     |
| Certificat RINA                     | 1SAA971000-0801     |
| Certificat UL                       | E191658-19880826    |

## Emballage

|                                |               |
|--------------------------------|---------------|
| Emballage Niveau 1<br>Unités   | box 1 pièce   |
| Emballage Niveau 1<br>Largeur  | 46 mm         |
| Emballage Niveau 1<br>Hauteur  | 70 mm         |
| Emballage Niveau 1<br>Longueur | 49 mm         |
| Emballage Niveau 1 Poids       | 0.255 kg      |
| Emballage Niveau 1 EAN         | 4013614543128 |
| Emballage Niveau 2<br>Unités   | box 10 pièce  |
| Emballage Niveau 2<br>Largeur  | 243 mm        |
| Emballage Niveau 2<br>Hauteur  | 80 mm         |
| Emballage Niveau 2<br>Longueur | 106 mm        |
| Emballage Niveau 2 Poids       | 2.61 kg       |
| Emballage Niveau 2 EAN         | 4013614543630 |

## Classifications

|                        |   |
|------------------------|---|
| Code de classification | Q |
|------------------------|---|

|                    |   |
|--------------------|---|
| d'objet            |   |
| ETIM 5             | EC000066 - Magnet contactor, AC-switching                                 |
| ETIM 6             | EC000066 - contacteur de puissance pour commutation de courant alternatif |
| ETIM 7             | EC000066 - Power contactor, AC switching                                  |
| ETIM 8             | EC000066 - Power contactor, AC switching                                  |
| eClass             | V11.0 : 27371003  |
| UNSPSC             | 39121529  |
| E-Number (Finland) | 3709688   |

---

## Catégories

---

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Contacteurs → Mini contacteurs

