

PRODUCT-DETAILS

E218-25-11

E218-25-11 Control Switch, 25 A, acc. to EN 250 V AC, 1NO, 1NC, 0CO, El. Color: Grey, MW: 0.5



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | E218-25-11 |
| Code de produit | 2CCA703051R0001 |
| EAN | 7612270938803 |
| Description courte | E218-25-11 Control Switch, 25 A, acc. to EN 250 V AC, 1NO, 1NC, 0CO, El. Color: Grey, MW: 0.5 |
| Description longue | Control switches according DIN EN 60669-1, VDE 0632 Part 1, Rated currents: 16/25 A, 250 VAC PDC, Contacts: 2 NO + 2 NC/3 NO + 1 NC/1 NO + 1 NC, Module width: 0,5/1 |

Technique

| | |
|----------------------------|--|
| Normes et standards | EN60669-1 VDE0632-1 IEC60068-2-2 IEC60068-2-1 IEC60068-2-38 UL508 |
| Tension nominale (U_r) | Minimum 250 V |
| Tension | acc. to EN 250 V AC acc. to UL 508 240 V AC |
| Type de tension | AC |
| Courant nominal (I_n) | 25 A |

| | |
|---|---|
| Pouvoir assigné de coupure de service en court-circuit (I_{cs}) | 3 kA |
| Fréquence assignée (f) | 50/60 Hz |
| Power Loss | 0.75 W |
| Number of Contacts CO | 0 |
| Number of Contacts NC | 1 |
| Number of Contacts NO | 1 |
| Number of Main Contacts NC | 1 |
| Number of Main Contacts NO | 1 |
| Number of Auxiliary Contacts CO (SPDT) | 0 |
| Nombre de pôles | 2 |
| Couple de serrage | 1.2-1.5 N·m |
| Switch Type | Double Interrupting Contacts |
| Material of Conductor | Copper |
| Options Provided | 1 NO + 1 NC |
| Remarques | Sealable in the On and Off positions |
| Cover Color | Grey |
| Control Element Color | Grey |
| Connecting Capacity | Solid 1x1...6 mm ² Solid 2x2.5 mm ² Flexible 1x0.75...2x2.5 mm ² |

Environnement

| | |
|---|--|
| Température de l'air ambiant | Operation -25...+55 °C Storage -40...+70 °C |
| Indice de protection | IP20 |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS | 2CCC441014D0201 |
| REACH Declaration | 2CCC005047D0201 |
| Informations environnementales | 2CCC441003C0201 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Dimensions

| | |
|-------------------------------------|-------|
| Width in Number of Modular Spacings | 0.5 |
| Produit Largeur Net | 9 mm |
| Produit Hauteur Net | 85 mm |
| Produit Longueur Net | 68 mm |
| Poids net | 44 g |
| Profondeur d'encastrement (t_2) | 68 mm |

Commande

| | |
|---------------------------|--------------|
| Emballage Niveau 1 Unités | box 10 pièce |
| Emballage Niveau 1 Poids | 495 g |
| E-Number (Finland) | 3602425 |
| E-Number (Switzerland) | 437254838 |

Certificats et Déclarations (Numéro de document)

| | |
|----------------------------------|-----------------|
| CB Certificate | 9AKK108466A3845 |
| CCC Certificate | 9AKK108466A3831 |
| Déclaration de Conformité - CE | 2CCC441014D0201 |
| Declaration of Conformity - UKCA | 9AKK108467A6137 |
| EAC Certificate | 9AKK107991A4779 |
| VDE Certificate | 9AKK107991A9822 |

Installation

| | |
|-------------------------|--------------------|
| Instructions et manuels | No document needed |
|-------------------------|--------------------|

Downloads Préférés

| | |
|--|-----------------|
| Fiche produit, informations techniques | 2CCC441003C0101 |
|--|-----------------|

Classifications

| | |
|--------------------------------|--|
| ETIM 8 | EC001545 - Main switch for distribution board |
| ETIM 9 | EC001545 - Main switch for distribution board |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 85365053 |
| eClass | V11.0 : 27142301 |
| Code de classification d'objet | S |

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Command and Signalling Devices → Control Switches, Pushbuttons and Indicator Lights

